

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 942 609 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
15.09.1999 Bulletin 1999/37

(51) Int. Cl.<sup>6</sup>: H04N 9/806

(21) Application number: 99104877.8

(22) Date of filing: 11.03.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventors:  
• Mori, Yoshihiro  
Hirakata-shi, Osaka (JP)  
• Kozuka, Masayuki  
Neyagawa-shi, Osaka (JP)

(30) Priority: 13.03.1998 JP 6335198

(74) Representative:  
Kügele, Bernhard et al  
NOVAPAT INTERNATIONAL SA,  
9, Rue du Valais  
1202 Genève (CH)


(71) Applicant:  
MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.  
Kadoma-shi, Osaka 571-8501 (JP)

## (54) Data storage medium, and apparatus and method for reproducing the data from the same

(57) A data storage medium having stored thereon includes an audio sequence including at least one audio stream; at least one video stream; and reproduction control information for controlling reproduction of the at least one audio stream and the at least one video stream. The reproduction control information includes

reproduction order information defining the order of at least one video stream, among the at least one video stream stored on the data storage medium, which is to be reproduced in synchronization with the audio sequence.

FIG. 8



EP 0 942 609 A1

## Description

### BACKGROUND OF THE INVENTION

#### 1. FIELD OF THE INVENTION:

[0001] The present invention relates to a data storage medium having still picture data and audio data stored thereon, and an apparatus and method for reproducing the still picture data along with high quality audio data.

#### 2. DESCRIPTION OF THE RELATED ART:

[0002] Conventionally known optical disks which music information including audio data or moving picture information is recorded to and reproduced from include compact disks (CDs) and laser disks (LDs). Compact disk recording and reproduction apparatuses and laser disk recording and reproduction apparatuses are conventionally known apparatuses for recording and reproducing the above-mentioned information.

[0003] A CD is an optical disk having a diameter of 12 cm for storing music information digitally recorded using an encoding technology referred to as linear PCM. CDs have been utilized as a medium for storing data for music applications. An LD is an optical disk having a diameter of 30 cm for storing moving picture information with audio data recorded as an analog signal. LDs have been utilized as a medium for storing data for video applications such as movies.

[0004] Recently, optical disks having a diameter of about 12 cm for storing music information and moving picture information including audio data digitally recorded. On such optical disks, either one or both of the music information and moving picture information are efficiently recorded in the state of being digitally compressed in order to acquire longer recording times and higher quality. Some of such optical disks have a file structure which facilitates data exchange with computers and communication apparatuses.

[0005] In order to meet demands for mediums having higher quality recording and reproduction of audio information than CDs, the DVD-Video technology has been developed and put into practice for realizing high quality audio data reproduction of linear PCM, 96 kHz and 24-bit sampling. However, the DVD-Video standards cannot provide high quality linear PCM multi-surround audio data reproduction or higher quality audio data reproduction. Accordingly, a higher quality technology has been in demand. However, the amount of high quality audio data is quite large and thus the reproduction speed of data required is quite high. Thus, it is difficult to record and reproduce image data along with the high quality audio data.

[0006] In the case of reproducing an audio title, there is a demand that the image data be used as supplemental data to the audio data as, for example, a so-called jacket picture such as lyrics and figure of the player. In

order to realize this, recording and reproduction apparatuses having more flexible and a wider variety of functions are required. The functions include reproduction of video data synchronously with high quality audio data, reproduction of video data asynchronously from audio data, manipulation of video data by key operation, and special effects at the time of video data switching.

[0007] There is another demand that data be reproduced as the title creator intended. For example, the initial operation when the disk is inserted should not be determined by the system used, and direct selection of the audio data should be permitted or prohibited in accordance with the intention of the title creator regardless of the type of the player.

[0008] Conventional optical disks, and recording and reproduction apparatuses generally have the above-described structure and thus have a problem in that it is difficult to record and reproduce high quality digital audio data along with video data. When the transfer speed of the high quality audio data is approximately equal to the reading speed of the optical disk, the video data cannot be reproduced along with the audio data by the method of multiplexing the audio data and the video data used in conventional apparatuses. The reason for this is that when the audio data and the video data are multiplexed, the transfer speed of the resultant data exceeds the reading speed of the optical disk and thus the continuous reproduction of such data cannot be guaranteed. The method, often used in computer applications, of appropriately buffering audio data and video data so as to simultaneously reproduce the audio data and the video data which are recorded on different areas of the optical disk cannot be used. The reason for this is that the sum of the transfer speeds of the audio data and the video data needs to be equal to or lower than the reproduction speed of the optical disk in order to continuously reproduce the data recorded on disks such as CDs for an hour or more.

[0009] A Browseable reproduction method of switching the video data based on an instruction by the user while continuously reproducing the audio data, or a Slide-Show reproduction method of automatically switching the video data in synchronisation with a specified position in the audio data are not usable.

#### SUMMARY OF THE INVENTION

[0010] According to one aspect of the invention, a data storage medium having stored thereon includes an audio sequence including at least one audio stream; at least one video stream; and reproduction control information for controlling reproduction of the at least one audio stream and the at least one video stream. The reproduction control information includes reproduction order information defining the order of at least one video stream, among the at least one video stream stored on the data storage medium, which is to be reproduced in synchronization with the audio sequence.

[0011] In one embodiment of the invention, the reproduction control information further includes video reproduction mode information indicating whether it is possible or not to change the order of the at least one video stream to be reproduced in synchronization with the audio sequence based on interaction from a user.

[0012] In one embodiment of the invention, the reproduction control information further includes video reproduction mode information indicating whether reproduction timing of the at least one video stream to be reproduced in synchronization with the audio sequence is defined or a reproduction time period thereof is defined.

[0013] In one embodiment of the invention, the reproduction control information further includes reproduction order mode information defining whether the at least one video stream, the order of which is defined by the reproduction order information, is reproduced randomly or sequentially,

[0014] In one embodiment of the invention, the reproduction order mode information indicates whether the at least one video stream is reproduced randomly while permitting overlap or randomly while prohibiting overlap.

[0015] In one embodiment of the invention, the audio sequence corresponds to at least one program, and the at least one video stream stored on the data storage medium is grouped on a program-by-program basis.

[0016] According to another aspect of the invention, an apparatus for reproducing information from a data storage medium having stored thereon an audio sequence including at least one audio stream; at least one video stream; and reproduction control information for controlling reproduction of the at least one audio stream and the at least one video stream, wherein the reproduction control information includes reproduction order information defining the order of at least one video stream, among the at least one video stream stored on the data storage medium, which is to be reproduced in synchronization with the audio sequence, the apparatus includes a reading section for reading the audio sequence and the at least one video stream stored on the data storage medium; and a reproduction section for reproducing the at least one video stream in synchronization with the audio sequence in the order defined by reproduction order information.

[0017] In one embodiment of the invention, the reproduction control information further includes video reproduction mode information indicating whether it is possible or not to change the order of the at least one video stream to be reproduced in synchronization with the audio sequence based on interaction from a user.

[0018] In one embodiment of the invention, the reproduction control information further includes video reproduction mode information indicating whether reproduction timing of the at least one video stream to be reproduced in synchronization with the audio sequence is defined or a reproduction time period thereof is defined.

[0019] In one embodiment of the invention, the reproduction control information further includes reproduction order mode information defining whether the at least one video stream, the order of which is defined by the reproduction order information, is reproduced randomly or sequentially.

[0020] In one embodiment of the invention, the reproduction order mode information indicates whether the at least one video stream is reproduced randomly while permitting overlap or randomly while prohibiting overlap.

[0021] In one embodiment of the invention, the at least one video stream to be reproduced in synchronization with the audio sequence is buffered into a buffer located in the reproduction apparatus before reproduction of the audio sequence.

[0022] According to still another aspect of the invention, a method for reproducing information from a data storage medium having stored thereon an audio sequence including at least one audio stream; at least one video stream; and reproduction control information for controlling reproduction of the at least one audio stream and the at least one video stream, wherein the reproduction control information includes reproduction order information defining the order of at least one video stream, among the at least one video stream stored on the data storage medium, which is to be reproduced in synchronization with the audio sequence, the method includes the steps of reading the audio sequence and the at least one video stream stored on the data storage medium; and reproducing the at least one video stream in synchronization with the audio sequence in the order defined by reproduction order information.

[0023] In one embodiment of the invention, the reproduction control information further includes video reproduction mode information indicating whether it is possible or not to change the order of the at least one video stream to be reproduced in synchronization with the audio sequence based on interaction from a user.

[0024] In one embodiment of the invention, the reproduction control information further includes video reproduction mode information indicating whether reproduction timing of the at least one video stream to be reproduced in synchronization with the audio sequence is defined or a reproduction time period thereof is defined.

[0025] In one embodiment of the invention, In one embodiment of the invention, the reproduction control information further includes reproduction order mode information defining whether the at least one video stream, the order of which is defined by the reproduction order information, is reproduced randomly or sequentially.

[0026] In one embodiment of the invention, the reproduction order mode information indicates whether the at least one video stream is reproduced randomly while permitting overlap or randomly while prohibiting overlap.

[0027] In one embodiment of the invention, the at least one video stream to be reproduced in synchronization

with the audio sequence is buffered into a buffer located in the reproduction apparatus before reproduction of the audio sequence.

[0028] According to still another aspect of the invention, in a data storage medium stored with a first system stream and a second system stream to be reproduced in synchronization with each other, the first system stream includes reproduction control information indicating timing at which the first system stream is reproduced, and the second system stream is reproduced at timing determined by information other than information included in the second system stream.

[0029] According to still another aspect of the invention, an apparatus for reproducing a data storage medium stored with a first system stream and a second system stream to be reproduced in synchronization with each other, the first system stream includes reproduction control information indicating timing at which the first system stream is reproduced includes a reading section for reading the first system stream and the second system stream stored on the data storage medium; and a decoder section for decoding the first system stream in accordance with the reproduction control information. The second system stream is decoded in accordance with a control signal supplied from outside of the decoder section.

[0030] According to still another aspect of the invention, a method for reproducing a data storage medium stored with a first system stream and a second system stream to be reproduced in synchronization with each other, wherein the first system stream includes reproduction control information indicating timing at which the first system stream is reproduced includes the steps of reading the first system stream and the second system stream stored on the data storage medium; and controlling the timing at which the first system stream is reproduced in accordance with the reproduction control information; controlling the timing at which the second system stream is reproduced in accordance with information other than information included in the second system stream.

[0031] Thus, the invention described herein makes possible the advantages of providing (1) an optical disk for realizing reproduction of high quality digital audio data along with video data in a restricted range of bit rates; (2) an optical disk, and an apparatus and method for reproducing data from such an optical disk for realizing switching between a mode in which high quality digital audio data and video data are reproduced synchronously with each other and a mode in which high quality digital audio data and video data are reproduced asynchronously from each other and the video data is switched based on time or by an instruction from the user; and (3) a reproduction apparatus for allowing a decoder used for a general MPEG2 stream to be used for reproducing audio data and video data as independent streams and thus for realizing reproduction of high quality digital audio data along with video data in a

restricted range of bit rates at a relatively low cost.

[0032] These and other advantages of the present invention will become apparent to those skilled in the art upon reading and understanding the following detailed description with reference to the accompanying figures.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0033]

Figure 1A is an external view of an optical disk in a first example according to the present invention;

Figure 1B is a cross-sectional view of the optical disk shown in Figure 1A;

Figure 1C is an enlarged cross-sectional view of the optical disk shown in Figure 1A;

Figure 1D shows pits formed in the optical disk in the first example according to the present invention;

Figure 2A shows a track structure of the optical disk shown in Figure 1A;

Figure 2B shows a sector structure of the optical disk shown in Figure 1A;

Figure 3 shows a logical structure of the optical disk shown in Figure 1A;

Figure 4 shows a data structure of an audio manager;

Figure 5 shows a data structure of an audio title set;

Figure 6 shows an exemplary structure of an audio object (AOB);

Figure 7 shows a data structure of PGC information and cell information;

Figure 8 is a block diagram showing an internal structure of a DVD player, which is a reproduction apparatus;

Figure 9 shows an example of PGC forming a title;

Figure 10 shows an example of program information;

Figure 11 shows an example of cell information;

Figure 12A shows a process for reproducing audio data without displaying a still picture;

Figure 12B shows a process for reproducing audio data without displaying a still picture;



Figure 13A shows a process for reproducing audio data while displaying a still picture;

Figure 13B shows a process for reproducing audio data while displaying a still picture;

Figure 14 shows a conventional process for reproducing audio data;

Figure 15 shows a schematic flow for reproducing a program;

Figure 16 shows a schematic flow for reproducing a leading audio cell;

Figure 17 shows a flow for reproducing a silent cell;

Figure 18 shows a flow for reproducing a continuously reproduced cell;

Figure 19 is a DVD player and peripheral devices connected thereto;

Figure 20 shows a remote controller used for operating the DVD player;

Figure 21 shows a logical structure of a DVD as a multimedia optical disk in a second example according to the present invention;

Figure 22 shows a structure of an audio manager;

Figure 23 shows a data structure of an AOB of the DVD in the second example;

Figure 24 shows an exemplary structure of the ROB;

Figure 25 shows a data structure of PGC information of the DVD in the second example;

Figure 26 is a block diagram showing an internal structure of a DVD player in the second example;

Figure 27 is a block diagram showing an internal structure of a DVD player including a system decoder for AOB and P\_VOB;

Figure 28 is a block diagram showing an internal structure of a DVD player including a P\_VOB buffer immediately before an AV decoder section;

Figure 29 shows the relationship among PGC, audio program, cell, picture program, picture cell, AOB and P\_VOB;

Figure 30 shows an example of program information forming a title;

Figure 31 shows a P\_VOB of the DVD in the second example;

Figure 32 shows an exemplary audio program;

Figure 33 shows another exemplary audio program;

Figure 34 shows the number of silent cell packs and audio cell packs of audio data of 48 kHz, 16-bit sampling and 2 channels;

Figure 35 shows picture cell information when the number of still picture packs is 50;

Figures 36A and 36B show methods for reproducing a silent cell and an audio cell;

Figure 37 is a flowchart illustrating a method for producing one of programs;

Figure 38 is a flowchart illustrating a method for producing one of the programs;

Figure 39 is a flowchart illustrating a method for producing one of the programs;

Figure 40 shows a video menu for allowing the user to select a title;

Figure 41 shows a structure of P\_PCI;

Figure 42 shows a structure of P\_DSI;

Figure 43 shows a logical structure of an optical disk in a third example according to the present invention;

Figure 44 shows a data structure of an audio manager (AMG);

Figure 45 shows a data structure of an audio still video set (ASVS);

Figure 46 shows a data structure of P\_VOB;

Figure 47 shows a data structure of highlight information;

Figure 48 shows a data structure of an audio title set (ATS);

Figure 49 shows a data structure of PGC information (ATS\_PGCI);

Figure 50 illustrates an audio still video display mode;

Figure 51 shows a data structure of an MPEG sys-

tem stream;

Figure 52 shows the relationship among P\_VOB, ASVU, ATS\_PGC1 and AOB;

Figure 53 shows an example of PGC information;

Figure 54 shows an example of audio program information (ATS\_PGI);

Figure 55 shows an example of ATS audio still video reproduction information (ATS\_ASV\_PBI);

Figure 56 shows an example of cell information;

Figure 57 shows an example of ASV search pointer;

Figure 58 shows an example of ASVU general information;

Figure 59A shows the relationship between the audio reproduction timing and the still picture display timing in the "SlideShow" mode;

Figure 59B shows the relationship between the audio reproduction timing and the still picture display timing in the "Browsable" mode;

Figure 60 illustrates an audio still video display mode;

Figure 61 is a block diagram illustrating an internal structure of a DVD player as a reproduction apparatus;

Figure 62 is a flowchart illustrating a method for reproducing PGC information;

Figure 63 is a flowchart illustrating a method for reproducing audio program;

Figure 64 is a flowchart illustrating a method for determining key operation;

Figure 65 is a flowchart illustrating a method for reproducing audio data;

Figure 66 is a flowchart illustrating a method for reproducing a still picture;

Figure 67 is a block diagram illustrating an internal structure of another DVD player as a reproduction apparatus;

Figure 68 is a block diagram illustrating an internal structure of still another DVD player as a reproduction apparatus; and

Figure 69 illustrates the relationship between DLIST and P\_VOB.

## DESCRIPTION OF THE EMBODIMENTS

[0034] Hereinafter, the present invention will be described by way of illustrative examples with reference to the accompanying drawings.

(Example 1)

[0035] An optical disk in a first example according to the present invention will be described.

(1) Physical structure of the optical disk

[0036] Figure 1A shows an external appearance of a DVD 107, which is a multimedia optical disk. Figure 1B shows a cross-section of the DVD 107 taken along line A-A' in Figure 1A. Figure 1C is an enlarged cross-sectional view of portion B shown in Figure 1B.

[0037] As shown in Figure 1B, the DVD 107 is formed by sequentially laminating a first transparent substrate 108, an information layer 109, an adhesive layer 110, a second transparent substrate 111, and a print layer 112 on which a label is to be printed in this order.

[0038] The first transparent substrate 108 and the second transparent substrate 111 are reinforcement substrates formed of the same material. In the example shown in Figure 1B, these substrates each have a thickness of about 0.6 mm. These substrates can each have a thickness in the range between about 0.5 mm and about 0.7 mm.

[0039] The adhesive layer 110 is provided between the information layer 109 and the second transparent substrate 111 in order to adhere the information layer 109 to the second transparent substrate 111.

[0040] On the face of the information layer 109 in contact with the first transparent substrate 108 is formed a reflective film (not shown) formed of a thin metal film or the like. By using a molding technique, a high density of convex and concave pits are formed in the reflective film.

[0041] Figure 1D shows the shapes of pits formed in the reflective film. In the example shown in Figure 1D, each pit has a length of 0.4  $\mu\text{m}$  to 2.13  $\mu\text{m}$ . A spiral track is formed in the DVD 107. The pits are formed alongside the spiral track so as to be at a distance of 0.74  $\mu\text{m}$  from the spiral track in a radial direction of the DVD 107. Thus, an array of pits are formed along the spiral track.

[0042] When a light beam 113 is directed toward the DVD 107, a light spot 114 is formed on the information layer 109 as shown in Figure 1C. The information stored on the DVD 107 is detected as a variation in the reflectance of the portion of the information layer 119 which is irradiated by the light spot 114.

[0043] The diameter of the light spot 114 of the DVD 107 is about 1/1.6 times the diameter of a light spot on

a CD because the numerical aperture (NA) of an object lens for DVDs is larger than the numerical aperture of an object lens for CDs and because the wavelength  $\lambda$  of a light beam for DVDs is shorter than the wavelength  $\lambda$  of a light beam for CDs.

[0044] A DVD having the above-described physical structure can store about 4.7 Gbytes of information on one side. A storage capacity of about 4.7 Gbytes is nearly 8 times the storage capacity of a conventional CD. Such a large storing capacity of DVDs can greatly improve the quality of moving pictures and also greatly extend the reproducible time period of moving pictures. Whereas the reproducible time period of a conventional video CD is 74 minutes, a DVD boasts a reproducible time period of 2 hours or more.

[0045] The fundamental technology which realizes such a large storing capacity lies in reduction of the spot diameter  $d$  of a light beam. The spot diameter  $d$  is calculated from the formula: spot diameter  $d$  = laser wavelength  $\lambda$ /numerical aperture NA of the object lens. Accordingly, the spot diameter  $d$  can be minimized by decreasing the laser wavelength  $\lambda$  and increasing the numerical aperture NA of the object lens. It should be noted, however, that increasing the numerical aperture NA of the object lens can result in coma aberration due to the relative slant of the optical axis of the light beam with respect to the face of the disk (i.e., "tilt"). In the case of DVDs, the coma aberration is minimized by reducing the thickness of a transparent substrate. However, reducing the thickness of a transparent substrate can result in another problem of lower mechanical strength of the disk. In the case of DVDs, the strength of the transparent substrate is reinforced by attaching another substrate to the transparent substrate, thereby overcoming the problems associated with the mechanical strength of the disk.

[0046] A red semiconductor laser having a short wavelength of 650 nm and an object lens having a large numerical aperture (NA) of about 0.6 mm are used to read the information stored on a DVD. By employing a thin transparent substrate having a thickness of about 0.6 mm in addition to the above-mentioned laser and object lens, it is possible to store about 4.7 Gbytes of information on one side of an optical disk having a diameter of 120 mm.

[0047] Figure 2A schematically illustrates a spiral track 20 formed from the inner periphery toward the outer periphery of the information layer 109 of the DVD 107 (Figure 1A). The spiral track 20 is divided into prescribed units referred to as sectors. In Figure 2A, the respective sectors are denoted by S1, S2, ..., S99, and S100. The information stored on the DVD 107 is read on a sector-by-sector basis.

[0048] Figure 2B shows an internal structure of a sector, where the sector includes a sector header region 21, a user data region 22, and an error correction code storage region 23. The sector header region 21 stores a sector address

[0049] for identifying the sector and an error detection code therefor. Based on these sector addresses, a disk reproduction apparatus determines one of a plurality of sectors from which information should be read.

[0050] The user data region 22 stores a 2 Kbyte long data string.

[0051] The error correction code storage region 23 stores error correction codes for the sector header region 21 and the user data region 22 included in the same sector. A disk reproduction apparatus performs error detection by using the error correction codes when reading data from the user data region 22 and performs error correction based on the error detection results, thereby insuring the reliability of data reading.

## (2) Logical structure of the optical disk

[0052] Figure 3 shows a logical structure of the DVD 107 (Figure 1A). As shown in Figure 3, the region of the DVD 107 is divided into a lead-in region 31, a volume region 32, and a lead-out region 33. These regions can be identified by identification information included in sector addresses of physical sectors. The physical sectors are arrayed in an ascending order based on their sector addresses.

[0053] In the lead-in region 31, data for stabilizing the operation of a reproduction apparatus at the beginning of read, for example, is stored.

[0054] No meaningful data is stored in the lead-out region 33. The lead-out region 33 is used for informing the disk reproduction apparatus of the termination of reproduction.

[0055] The volume region 32 stores digital data corresponding to an application. The physical sectors included in the volume region 32 are managed as logical blocks. The logical blocks are identified by sequential numbers (logical block numbers) respectively assigned to the physical sectors after the first physical sector (designated as the 0th physical sector) in the volume region 32.

[0056] As shown in Figure 3, the volume region 32 is subdivided into a volume file management region 32a and an audio zone region 32c.

[0057] The volume file management region 32a stores file system management information for managing a plurality of logical blocks as files in accordance with ISO13346. The file system management information is information indicating the correspondence between the name of each of a plurality of files and the addresses of the logical blocks occupied by that file. A disk reproduction apparatus achieves file-by-file access to the optical disk based on the file system management information. Specifically, the disk reproduction apparatus refers to the file system management information to obtain the addresses of the logical blocks corresponding to a given file name, and accesses the logical blocks based on these addresses. As a result, the digital data contained in a desired file can be read.

[0058] An audio zone region 32c stores an audio manager 900 and one or more audio title sets 800.

[0059] The audio title set 800 contains a plurality of pieces of audio data and management information for managing the order of reproducing the plurality of pieces of audio data. An audio title set 800 has a data structure which allows for management of the audio data in units which are referred to as audio titles. Typically, an audio title corresponds to a music album containing one or more tunes.

### (3) Data structure of the audio zone region 32c

[0060] The audio zone region 32c stores an audio manager 900 and one or more audio title sets 800.

#### (3.1) Data structure of the audio title set 800

[0061] Figure 5 shows a data structure of an audio title set 800. The audio title set 800 includes a plurality of audio objects (hereinafter, referred to as "AOBs") 802, audio title set management information (ATSI) 801 for managing the order of reproducing the plurality of AOBs 802, and audio title set management information backup (ATSI\_BUP) 804 which is backup data of the audio title set management information 801. In the following description, an "audio title set" will generally be referred to as an "ATS".

##### (3.1.1) Data structure of the AOB 802

[0062] The AOB 802 is packetized into 2 Kbytes. The AOB 802 stores data in the LPCM format, AC3 format, DTS format or other compression formats. In the case of the LPCM format, the sample bit is 16, 20, or 24 bits, with a sampling frequency of 48 kHz, 96 kHz, 192 kHz, 44.1 kHz, 88.2 kHz, or 176.4 kHz.

##### (3.1.2) Data structure of the audio title set management information 801

[0063] The audio title set management information (ATSI) 801 includes information for managing the order of reproducing the AOBs 802. The order of reproducing the AOBs 802 is designated by a program chain (PGC), as in the case of video objects (VOBs). Different PGCs can define different orders of reproduction of AOBs 802.

[0064] As shown in Figure 5, the audio title set management information (ATSI) 801 includes an ATS management table (ATSI\_MAT) 811 and a PGC management information table (ATS\_PGCIT) 812.

[0065] The ATS management table 811 serves as header information of the audio title set management information 801. The ATS management table 811 includes a pointer indicating a region in which each AOB 802 is stored, a pointer indicating a region in which the PGC management information table 812 is stored, and attribute information on each AOB 802. In the case

where a still picture is stored on the DVD 107 (Figure 1A), the ATS management table 811 also includes attribute information and the like for the still picture.

[0066] The PGC management information table (ATS\_PGCIT) 812 includes ATS PGC management table information (ATS\_PGCITI) 831, a plurality of ATS PGC information search pointers (ATS\_PGCI\_SRP) 832, and a plurality of PGC information (ATS\_PGCI) units 833.

[0067] The ATS PGC information search pointers (ATS\_PGCI\_SRP) 832 are indices for a plurality of PGCs stored in the PGC management information table 812 and designate the PGC information to be executed first on a title-by-title basis.

[0068] Each of the PGC information units describes positions on the optical disk 107 where one or more audio objects are recorded and the order of reproduction thereof. Reproduction of the same audio object can be described by different PGC information. Specifically, each PGC information unit includes "ATS PGC general information (ATS\_PGC\_GI)", "ATS program information table (ATS\_PGIT)", and "audio cell reproduction information table (ATS\_C\_PBIT)".

[0069] Figure 7 shows a data structure of each PGC information unit. As shown in Figure 7, "ATS PGC general information (ATS\_PGC\_GI)" includes the number of programs and the number of cells included in the PGC information, the reproduction time period of the PGC, and information on pointers to "ATS program information table (ATS\_PGIT)" and to "audio cell reproduction information table (ATS\_C\_PBIT)".

[0070] The "ATS program information table (ATS\_PGIT)" includes "program physical allocation information" indicating whether or not the AOB of each program and the AOB of the previous program are recorded at physically discontinuous positions on the optical disk, "program time attribute information" indicating whether or not the time information of the AOB is continuous with the time information of the previous AOB, "program start cell number" indicating the first cell number forming the program, "program still picture flag" indicating whether or not the program includes a still picture, "reproduction start audio cell time" indicating the first time information of the first audio cell included in the program, "program total reproduction time period" indicating the reproduction time period of the program, and "audio pause time period" indicating the silent period until the reproduction of the audio cell of the program starts.

[0071] The "audio cell reproduction information table (ATS\_C\_PBIT)" stores cell information forming the AOB to be reproduced. Specifically, the "ATS cell reproduction information table" includes "cell index number" indicating the order of cells included in the program, "cell type" indicating the attribute of the cell (i.e., whether the cell is a still picture cell, a silent cell or an audio cell), "cell start address" indicating the start address of the cell in the form of a relative address with respect to the

first pack of the AOB of the ATS including the cell, and "cell termination address" indicating the final address of the cell in the same manner.

[0072] Figure 6 shows an exemplary structure of the AOB. The AOB is part of an MPEG2 stream and includes a still picture cell including a still picture pack, a silent cell including an audio pack including substantially silent audio data, and an audio cell including an audio pack of audio data forming a tune. The AOB includes one or more audio cells and may not include a still picture cell or a silent cell. Still picture cells are never continuous with each other and silent cells are never continuous with each other. A still picture cell is always followed by a silent cell or an audio cell. A silent cell is always followed by an audio cell. In the example shown in Figure 6, audio cells and silent cells exist and are physically continuous. Time information is also continuous; i.e., the "program physical allocation information" has a value representing "continue", and the "program time attribute information" also has a value representing "continue".

[0073] In Figure 6, the line passing through points B, C, E, F and G represents a change in the value of the time information (i.e., PTS) of the AOB. Point A represents a value of the PTS of the still picture cell. Point B represents a value of the first PTS of a silent cell. Point C represents a value of the first PTS of an audio cell. Thus, the PTS of a silent cell is continuous to the PTS of an audio cell, and there is no data underflow gap, as referred to with respect to the MPEG2 stream, between the silent cell and the audio cell. Point B, at which the value of the PTS of the silent cell is larger than the value of the PTS of the still picture cell, represents that a still picture in the still picture cell is displayed before the reproduction of the silent cell starts. The PTS of the next still picture cell is represented by point D, and the PTS of the next silent cell is represented by point E. In the case where the PTS of the still picture cell and the PTS of the silent cell have an equal value, the reproduction of the silent cell starts simultaneously when the still picture is displayed. The difference between the first PTS of the next audio cell at point F and the final PTS of the audio cell at point D is "audio pause time period". Since the gap between the PTS's needs to be 0.7 seconds or less as specified by MPEG2, the difference at point B between the first PTS of the silent cell and the PTS of the still picture cell, and the difference at point D between the first PTS of the still picture cell and the final PTS of the audio cell need to fulfill such a condition.

[0074] Figure 9 shows an exemplary PGC forming a title. The example shown in Figure 9 includes five programs. Programs #1 and #2 correspond to AOB #1, and programs #3, #4 and #5 correspond to AOB #2. On the information storing medium, AOB #1 is recorded after AOB #2. Programs #1 and #2 both include a still picture cell and a silent cell, and program #2 includes two audio cells. Programs #3 and #4 include only a silent cell, and program #5 includes only an audio cell.

[0075] In the case where all the audio cells each have a reproduction time period of 60 seconds (5,400,000 in PTS), all the silent cells each have a reproduction time period of 1 second (90,000 in PTS), and the PTS of the still picture cell has the same value as that of the first PTS of the silent cell, program information can be described as shown in Figure 10. Under the conditions that the size of the still picture data is about 1.88 Mbits and the audio data is 48 kHz, 16 bit sampling with 2 channels, the number of the still picture packs is 112, the number of the silent cell packs is 96, and the number of the audio cell packs is 5760 as shown in Figure 11.

[0076] The audio title set has been described. Next, with reference to Figure 4, the audio manager will be described.

### (3.2) Data structure of the audio manager 900

[0077] The audio manager 900 is information for controlling the reproduction which is to be first referred to for performing audio-oriented reproduction of the information on the optical disk by a reproduction apparatus.

[0078] Figure 4 shows a data structure of the audio manager 900.

[0079] The audio manager 900 includes "audio manager information (AMGI)", "VOB for audio manager menu (AMGM\_VOBS)", and "audio manager information backup (AMGI\_BUP)".

[0080] The "audio manager information (AMGI)" includes "audio manager information management table (AMGI\_MAT)" including attribute information and pointer information, "audio title management information" indicating the number of audio titles and the like, "audio title search pointer (ATT\_SRP)" indicating search information on the audio titles, and "audio manager menu PGC management information table (AMGM\_PGC\_MAT)" indicating PGC information for audio manager menu.

[0081] Each "audio title search pointer (ATT\_SRP)" includes "audio title type" indicating the type of each title, "number of programs in the titles" indicating the number of programs included in the titles, "title reproduction time period" indicating the reproduction time period of the titles, "ATS number" indicating the set number of the ATS to which each title belongs, "ATS title number" indicating the title number of each title in the ATS, and "ATS address" indicating the address of the ATS to which each title belongs.

[0082] The audio zone region and the DVD as a multimedia optical disk have been described. Next, a reproduction apparatus according to the present invention will be described.

[0083] First, an external appearance of a DVD player, which is a reproduction apparatus for multimedia optical disks will be described. Figure 19 shows external appearances of a DVD player 1, a TV monitor 2 and a remote controller 91.

[0084] The DVD player 1 has an opening in a front face of a chassis thereof, and includes a driving mechanism for loading an optical disk in the depth direction of the opening.

[0085] Provided on the front face of the DVD player 1 is a remote control receiving section 92 having a light receiving element for receiving infrared rays emitted by the remote controller 91. When an operator uses a remote controller held in his/her hand, the remote control receiving section 92 sends an interrupt signal indicating that a key signal has been received.

[0086] Provided on a rear face of the DVD player 1 are video and audio output terminals. A video signal reproduced from the DVD can be output to the large TV monitor 2 for home use by connecting an AV cord to the video and audio output terminals. Thus, the operator can enjoy the video reproduced from the DVD on a large TV of, for example, 33 inches or 35 inches. As can be appreciated from the above description, the DVD player 1 in this example is not used in the state of being connected to a personal computer but is used with the TV monitor 2 as an electronic appliance for home use.

[0087] The remote controller 91 includes a spring-loaded keypad on a surface of a casing thereof, and outputs a code corresponding to a pressed key by infrared rays. Figure 20 shows an operation panel of the remote controller 91. The "POWER" key on the operation panel is for turning the DVD player 1 ON or OFF. The "MENU" key is used for retrieving the volume menu of the optical disk during reproduction of the program chain. Ten keys are used for, for example, chapter-jumping the movie or selecting music tunes. Upward, downward, leftward and rightward cursor keys are used for selecting items. The "ENTER" key is used for confirming an item selected by the cursor. When the cursor is moved on items by the upward, downward, leftward and rightward cursor keys, the item on which the cursor is positioned is displayed with a select color of item color information of the management information pack. When the item is confirmed by the "ENTER" key, the item is displayed with a confirmation color. In addition, there are keys which are common with other AV apparatuses such as, for example, "PLAY", "STOP", "PAUSE", "FORWARD" and "REWIND" keys.

[0088] Next, the structure of the DVD player, which is a reproduction apparatus for multimedia optical disks will be described.

[0089] Figure 8 is a block diagram of an internal structure of a DVD player 70. The DVD player 70 includes a driving mechanism 81, an optical pickup 82, a mechanism control section 83, a signal processing section 84, an AV decoder section 85, a remote control receiving section 92 and a system control section 93.

[0090] The driving mechanism 81 includes a table on which an optical disk is set and a spindle motor for clamping and rotating the optical disk which is set on the table. The table is structured to be moved in and out of the chassis by an eject mechanism not shown. When

the table is out of the chassis, the operator sets an optical disk onto the table. When the optical disk is set on the table and the table is moved back into the chassis, the optical disk is loaded on the DVD player 70.

[0091] The mechanism control section 83 controls a mechanical system including the motor for driving the disk and the optical pickup 82 for reading a signal recorded on the disk. Specifically, the mechanism control section 83 adjusts the motor speed in accordance with the position of the track indicated by the system control section 93. The mechanism control section 83 also controls an actuator of the optical pickup 82 to move the optical pickup 82. When an accurate track is detected by servo control, the mechanism control section 83 instructs the optical disk to wait until a desired physical sector on the rotating optical disk reaches the position of the optical pickup 82. Then, signals are continuously read from the desired position.

[0092] The signal processing section 84 processes the signal read from the optical pickup 82 with, for example, amplification, waveform shaping, binarization, demodulation, and error correction to convert the signal into a digital data stream, and then stores the resultant data stream in a buffer memory in the system control section 93 (described below) on a logical block-by-logical block basis.

[0093] The AV decoder section 85 processes the digital data, which is an input VOB, in a prescribed manner to convert the data into a video signal or an audio signal. Specifically, the AV decoder section 85 includes a system decoder 86, a video decoder 87 and an audio decoder 88.

[0094] The system decoder 86 receives the digital data stream transferred from the buffer memory on a logical block-by-logical block basis (i.e., on a packet-by-packet basis) and distinguishes a stream ID and a sub stream ID in the header of each packet, thereby classifying the data into a moving picture data pack, an audio data pack and a management information pack. At this point, the moving picture data pack is output to the video decoder 87. Regarding the audio data pack, only an audio data pack having a designated stream number is output to the audio decoder 88 in accordance with a decode stream instruction command sent from the system control section 93. The management information pack is output to the system control section 93. The moving picture data pack input to the video decoder 87 is extended by the prescribed format defined by the MPEG2 format and output as digital video data. Then, the digital video data is converted into a video signal of the NTSC format and externally output. The audio data input to the audio decoder 88 is decoded in the LPCM or AC3 format in accordance with the data type, D/A converted, and then externally output as an audio signal.

[0095] The audio decoder 88 processes the digital data, which is an input AOB, in a prescribed manner in accordance with the data type, converts the data into an audio signal, and externally outputs the data.



[0096] The system control section 93 includes a working memory and a CPU integrated together and performs the overall control of the DVD player 70.

[0097] The reproduction apparatus according to the present invention operates in, for example, the following manner.

[0098] When a DVD is loaded in the DVD player 70, the system control section 93 detects that a DVD is loaded from the optical sensor or the like. Then, the system control section 93 controls the mechanism control section 83 and the signal processing section 84, thereby controlling rotation of the DVD so as to cause the optical pickup 82 to seek to the lead-in region. Thus, the DVD player 70 is initialized and reproduction starts.

[0099] For starting the reproduction, the system control section 93 determines whether or not the DVD player 70 is in a video-oriented reproduction mode, by a reproduction mode determination section. When it is determined that the DVD player 70 is in the video-oriented reproduction mode, the system control section 93 reads the video manager based on the information which is read from the volume file management region. The system control section 93 refers to the PGC management information table for the video manager menu to calculate the recording address of the PGC for the volume menu. The resultant PGC is reproduced and retained inside. When the PGC for the volume menu is retained inside, the system control section 93 refers to the retained PGC information to calculate the video object (VOB) to be reproduced and the recording address of the VOB on the optical disk. When the VOB to be reproduced is determined, the system control section 93 outputs a control signal to the mechanism control-section 83 and the signal processing section 84 so as to retrieve the determined VOB from the DVD for reproduction. Thus, the video menu from which the user can select the title to be reproduced is displayed.

[0100] The user sees the menu and selects and confirms the title that he/she is interested in by designating the item number in the menu using the remote controller. Then, the system control section 93 receives the designation of the item number in the menu from the remote controller and refers to the management information pack included in the VOB of the video menu which is being reproduced, the VOB being input from the AV decoder section 85, to execute a control command corresponding to the designated number. The control command is PlayTitle #n or the like, and the title number to be reproduced is designated by "n". As an execution operation by the PlayTitle command, the system control section 93 refers to the title search pointer table, which is a part of the audio manager, to determine the audio title set (ATS) to which the designated title belongs to and the title number in the ATS. When the ATS is confirmed, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to reproduce the ATS management information of the confirmed title

set and retrieves the title search pointer table of the ATS, which is a part of the ATS management information, to the system control section 93. When the title search pointer table is retrieved, the system control section 93 refers to the table to determine the PGC information for starting the reproduction of the title to be reproduced. When the PGC information is determined, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to reproduce the determined PGC information and retain the information in the inside buffer memory for the PGC information. When the PGC information is retained, the system control section 93 refers to the retained PGC information to determine the audio object (AOB) to be reproduced and the recording address thereof. Then, the AOB is reproduced by a control signal output to the mechanism control section 83 and the signal processing section 84 from the system control section 93.

[0101] The system control section 93 sequentially determines the AOBs to be reproduced and controls the reproduction thereof in accordance with the retained PGC information. When the reproduction of the final AOB indicated by the PGC information is completed, the system control section 93 searches for the PGC information of the next title and reproduces the AOBs described in the PGC information in the same manner. Thus, all the titles are reproduced and the operation is stopped. In accordance with specific setting of the DVD player or the DVD, only one title can be reproduced before the operation is stopped, or a menu can be displayed after reproduction of one or more titles is completed.

[0102] Next, a method for reproducing a still picture cell, a silent cell and an audio cell will be described in detail.

[0103] Figure 14 shows a conventional method for reproducing the audio cell. Conventionally, for reproducing an MPEG2 stream, the leading end of the audio cell pack is first sought and data reading starts. However, audio output does not immediately start but starts after an idle time period, which is predetermined in each reproduction apparatus. The idle time period includes a time period required for determining the PTS of the audio data, a time period required for determining that data is correct, and a time period required for the muting circuit in an analog output section to be transitioned from a mute state to a non-mute state. Thus, the idle time period varies in accordance with the type of reproduction apparatus. Especially when the reproduction section and the decoder are accommodated in separate chassis, the idle time period tends to be extended because determination on the PTS and the determination on the correctness of the audio data are separately performed.

[0104] Figures 12A and 12B show methods for reproducing only audio data without displaying a still picture even though the still picture is included. Figure 12A



shows the method in the case where the reproduction is performed from the leading end of the data, and Figure 12B shows the method in the case where the reproduction is performed in continuation from the previous cell.

[0105] In the case where reproduction is performed from the leading end of the data by selecting a title or program from the menu or the like through jumping, the leading pack of the silent cell is jumped to with reference to the start address of the cell information. At this point, the STC, which is the reference time of the decoder is set with the SCR of the leading pack of the silent cell. Next, skipping and jumping of data corresponding to a prescribed idle time period are performed with reference to the PTS of the silent cell, and the silent cell for the idle time period is reproduced. Audio output is prepared for during this period. At this point, the next title number is not displayed on the display device of the reproduction apparatus, and the passage of reproduction time period is not updated. In the case where the audio output is started and display of the title number and the updating of the passage of the reproduction time period are performed simultaneously when the first PTS of the leading cell is detected, the reproduction apparatus behaves as if the audio data is output simultaneously with the completion of the jump such as menu selection. In the case where the reproduction is performed in continuation from the previous cell, a still picture pack is jumped over and a silent cell is jumped over or skipped except for the idle time period. At this point, by continuously counting the STC, which is reference for the system time, the interval between the completion of the audio output by the previous cell and the start of the audio output by the next cell equals the audio pause time period. The counting of the STC is continued when the physical allocation information and the time attribute information both have a value indicating "continue". When either one of them indicates "no-continue", the same processing as in the jump from the menu is performed, and thus the STC is reset at the leading end of the silent cell pack. Even in the case where there is no still picture cell, the method is substantially the same as described above. In the case where there is no silent cell and the reproduction starts from the leading end of the data, the operation is similar to the conventional operation shown in Figure 14. In the case where the reproduction is performed in continuation from the previous cell, the operation is as follows. When the time attribute information indicates "continue", the audio cell is decoded continuously from the previous cell and audio data is output. When the time attribute information indicates "no-continue", the operation is the same as the conventional operation shown in Figure 14 as in the case where the reproduction is performed from the leading end of the data.

[0106] Figures 13A and 13B show methods for reproducing the audio data while displaying a still picture. Figure 13A shows the method in the case where the reproduction is performed from the leading end of the

data, and Figure 13B shows the method in the case where the reproduction is performed in continuation from the previous cell.

[0107] In the case where the reproduction is performed from the leading end of the data or by selecting a title or program from the menu or the like through jumping, the pack of the still picture cell is sought from the cell information. Thus, the still picture cell is read and decoded. At this point, the STC, which is the reference time of the decoder, is set with the SCR of the leading pack of the still picture cell. Next, the leading pack of the silent cell is read. When an STC reaches an STC of the still picture cell, the still picture is displayed. The rest of the operation is the same as the operation when there is no still picture. The display of the still picture can be during the processing of the silent cell, simultaneously with the start of output of the audio cell, or after the start of output of the audio cell in the range permitted by the MPEG2 format. In the case where the reproduction is performed in continuation from the previous cell, the still picture cell is read and decoded when a still picture pack is detected. Next, the silent cell is processed. Whether or not the STC is set depends on the time attribute information as in the case where there is no still picture cell. The rest of the operation is the same as the operation when no still picture is displayed, except that the still picture is displayed when the STC becomes a PTS of the still picture cell and that the STC is set with the SCR of the leading pack of the still picture cell.

[0108] Figures 15 through 18 are flowcharts each illustrating a program. In the case where the physical allocation information of the program information shows "continue" and the program previously reproduced has a program number which is smaller by one than the program number of the program to be reproduced now, seek to the reading head for the DVD is not specifically necessary. When the time attribute information indicates "continue" and the reproduction is performed in continuation from the previous program, the STC, which is the reference time for the decoder, does not need to be reset.

[0109] The determination of whether or not the cell is a still picture cell can be performed using the cell type in the cell information or using a still picture flag of the program information. The determination of whether or not the cell is a silent cell is performed by the cell type in the cell information. The determination that the cell is the final cell is performed by comparing the termination address of the cell information and the address read from the data in the DVD. The completion of the reproduction of the program can be determined by the cell index of the cell information returning to zero, the cell type indicating a still picture cell or a silent cell, or the start cell number of the next program in the program information.

[0110] The skipping of the silent cell is performed while detecting the PTS when the silent cell is decoded

or by obtaining the number of packs to be skipped based on the data rate.

[0111] As described above, in the first example according to the present invention, program reproduction information including the start time and reproduction time period of each of audio data based on the reproduction start time of the leading audio data in an MPEG2 stream is recorded in the management region as a part of the reproduction control information. Accordingly, a multimedia information storing medium which realizes reproduction of high quality digital audio data and video data added thereto under a restricted bit rate can be provided. The interval between the reproduced audio data can be uniform even in low-cost reproduction apparatuses or reproduction apparatuses having no reproduction function for video data. Thus, title creators can prepare data easily.

#### (Example 2)

[0112] An optical disk, and an apparatus and method for reproducing information from the optical disk in a second example according to the present invention will be described. Identical elements previously discussed in the first example bear identical reference numerals and the descriptions thereof will be omitted.

#### (1) Physical structure of the optical disk

[0113] The physical structure of the optical disk is identical with that described in the first example and thus the description thereof will be omitted.

#### (2) Logical structure of the optical disk

[0114] The logical structure of the optical disk is identical with that described in the first example and thus the description thereof will be omitted.

#### (3) Data structure of the audio zone region 32c

[0115] The audio zone region 32c stores an audio manager 900 and one or more audio title sets 800 as in the first example. The data structure of the audio manager 900 and the data structure of the audio title sets 800 are different from those in the first example.

##### (3.1) Data structure of the audio title set 800

[0116] Figure 23 shows a data structure of the audio title set 800 in the second example. The audio title set 800 includes a plurality of audio objects (hereinafter, referred to as "AOBs") 802, a plurality of picture video objects (hereinafter, referred to as "P\_VOBS" 1002), audio title set management information (ATSI) 801 for managing the order of reproducing the plurality of AOBs 802 and the plurality of P\_VOBS 1002, and audio title set management information backup (ATSI\_BUP) 804

which is backup data of the audio title set management information 801. In the following description, an "audio title set" will generally be referred to as an "ATS".

##### (3.1.1) Data structure of the AOB 802

[0117] The data structure of the AOB 802 of the optical disk is identical with that described in the first example and thus the description thereof will be omitted.

##### (3.1.2) Data structure of P\_VOB 1002

[0118] Figure 31 shows a data structure of the P\_VOB 1002. The P\_VOB 1002 includes a picture NV pack (P\_NV\_PCK) 1003, a plurality of video packs (V\_PCK) 1004, and a plurality of sub-picture packs (SP\_PCK) 1005.

[0119] Unlike in the case of DVD-Video, the P\_VOB 1002 includes one picture video object unit (P\_VOBU), and only one picture NV pack (P\_NV\_PCK) 1003 is included.

[0120] The sub-picture packs (SP\_PCK) 1005 can each have a plurality of sub-picture streams and has an identification code as in the case of DVD-Video. The sub-picture packs (SP\_PCK) 1005 can be omitted.

[0121] The P\_VOB 1002 does not include audio data, unlike in the case of DVD-Video. The picture NV pack (P\_NV\_PCK) 1003 includes a P\_PCI packet and a P\_DSI packet in a similar manner as a PCI packet and a P\_DSI packet of DVD-Video.

[0122] As shown in Figure 41, the P\_PCI includes P\_VOBU to which the P\_PCI belongs to (i.e., attribute information, reproduction time information, highlight information and the like of P\_VOB), as in the case of DVD-Video, but does not include address information.

[0123] As shown in Figure 42, the P\_DSI includes an SCR of the NV\_PCK to which the P\_DSI belongs, and a termination address of the P\_VOBU, i.e., P\_VOB to which the P\_DSI belongs, and address information of a pack including the final data of the first I picture of the video pack (P\_PCK) as in the case of DVD-Video, but does not include other information.

##### (3.1.3) Data structure of the audio title set management information 801

[0124] The audio title set management information (ATSI) 801 includes information for managing the order of reproducing the AOBs 802 and the P\_VOB 1002. The order of reproducing the AOBs 802 is designated by a program chain (PGC), as in the case of video objects (VOBs).

[0125] The data structure of the audio title set management information 801 is identical with that shown in Figure 5 except for the data structure of the PGC information 833.

[0126] Each of the PGC information units describes positions on the optical disk where one or more audio

objects are recorded and the order of reproduction thereof. Reproduction of the same audio object can be described by a different PGC information unit. Specifically, the PGC information includes "ATS PGC general information (ATS\_PGC\_GI)", "ATS program information table (ATS\_PGIT)", "audio cell reproduction information table (ATS\_C\_PBIT)", "ATS picture program information table (ATS\_PPGIT)", and "ATS picture cell reproduction information table (ATS\_PC\_PBIT)".

[0127] Figure 25 shows a data structure of the PGC information. As shown in Figure 25, "ATS PGC general information (ATS\_PGC\_GI)" includes the number of picture programs, the number of audio programs and the number of cells included in the PGC information; the reproduction time period of the PGC; and information on pointers to a picture program reproduction mode, picture program reproduction control, the "ATS program information table (ATS\_PGIT)", "audio cell reproduction information table (ATS\_C\_PBIT)", "ATS picture program information table (ATS\_PPGIT)", and "ATS picture cell reproduction information table (ATS\_PC\_PBIT)".

[0128] The "ATS program information table (ATS\_PGIT)" includes a plurality "audio program information (ATS\_PGI)" units included in the PGC. Each of the plurality of "audio program information (ATS\_PGI)" units includes "audio program physical allocation information" indicating whether or not the AOB of each program and the AOB of the previous program are recorded at physically discontinuous positions on the optical disk, "audio program time attribute information" indicating whether or not the time information of the AOB is continuous with the time information of the previous AOB, "audio program start cell number" indicating the first cell number forming the audio program, "reproduction start audio cell time" indicating the first time information of the first audio cell included in the audio program, "audio program total reproduction time period" indicating the reproduction time period of the audio program, and "audio pause time period" indicating the silent period until the reproduction of the audio cell of the audio program starts.

[0129] The "audio cell reproduction information table (ATS\_C\_PBIT)" stores cell information forming the AOB to be reproduced as in the first example.

[0130] The "ATS picture program information table (ATS\_PPGIT)" includes a plurality of "ATS picture program information" units. Each ATS picture program information unit includes a used SP number (PPG\_SP\_STN) describing a stream number of a sub-picture used in the picture program, an initial button number (PPG\_FOSL) indicating the number of a button which is in the highlight information used in the picture program and is selected in an initial state, a picture transition mode (PPG\_T\_mode) indicating a transition mode of a still picture in the program, a still picture identification code (PPG\_ISRC\_SPCT) indicating an ISRC code of the still picture in the program, a picture cell start PTS (PC\_S\_PTM) indicating a PTS of a first pack

of the picture cell of the program, a picture program reproduction time period (ATS\_PPG\_PB\_TM) which is a reproduction time period of the program, a start section transition time period (PPG\_TI\_TM) indicating the transition time period at the time of starting the reproduction of the still picture of the program, and a termination section transition time period indicating the transition time period at the time of terminating reproduction of the still picture of the program.

[0131] In this example, as the picture transition modes, "no transition", "fading from black", "fading into black", "cross-fading", and "wiping in several directions" are assumed. Each of the programs includes one cell. Since each cell has an independent P\_VOB, the reproduction time period of the picture program is a 1-frame time period.

[0132] The "ATS picture cell reproduction information table (ATS\_PC\_PBIT)" includes a cell still time period (P\_C\_Still\_Time) indicating a continuous time period during which the picture cell is displayed, a start address (P\_C\_FVOBU\_SA) of a cell of the picture program, and a termination address (P\_C\_LVOBU\_SA) indicating an address of the final packet of the cell.

[0133] Figure 24 shows an exemplary structure of the AOB. The AOB is a part of an MPEG2 stream and includes a silent cell including an audio pack including substantially silent audio data and an audio cell including an audio pack of audio data forming a tune. The AOB includes one or more audio cells and may not include a silent cell. A silent cell is never followed by another silent cell and is always followed by an audio cell. In the example shown in Figure 24, audio cells and silent cells exist and are physically continuous. Time information is also continuous; i.e., the "audio program physical allocation information" has a value representing "continue", and the "audio program time attribute information" also has a value representing "continue".

[0134] In Figure 24, the line passing through points B, C, E, F and G represents a change in the value of the time information (i.e., PTS) of the AOB. Point B represents a value of the first PTS of a silent cell. Point C represents a value of the first PTS of an audio cell. Thus, the PTS of a silent cell is continuous to the PTS of an audio cell, and there is no data underflow gap, as referred to with respect to the MPEG2 stream, between the silent cell and the audio cell. In a similar manner, the PTS of the next silent cell is represented by point E. The difference between the first PTS of the next audio cell at point F and the final PTS of the audio cell at point D is an "audio pause time period". Since the PTS's need to be continuous in one stream as specified by MPEG2, the change in the PTS is linear as shown in Figure 24.

[0135] With reference to Figures 31, 41 and 42, the picture video object (P\_VOB) will be described in detail. As described above, the leading pack of the P\_VOB 1002 is a picture NV pack (P\_NV\_PCK) 1003 including a P\_PCT packet and a P\_DSI packet having time information, position information and highlight information.

Only one picture NV pack (P\_NV\_PCK) 1003 always exists at the leading end thereof. The picture NV pack (P\_NV\_PCK) 1003 is followed by video packs (V\_PCK) 1004 which are MPEG2 video packs for storing video data and sub-picture packs (SP\_PCK) 1005 for dividing sub-picture streams which are permitted to be included up to 32 streams and storing the divided sub-picture streams. In Figure 31, 2 sub-picture streams 1005 (SP#1 and SP#2) are included and each sub-picture stream is divided into 2 packs. In Figure 31, the video packs (V\_PCK) 1004 precede the sub-picture packs (SP\_PCK) 1005, but there is no limitation regarding the order as long as the MPEG2 standards are fulfilled. Although termination codes such as program encodes or the like are not shown in Figure 31, such termination codes can be included as long as the requirements of MPEG2 streams are fulfilled. Such termination codes need not be included since the P\_VOB 1002 is a part of the MPEG2 program stream.

[0136] Figure 41 shows a structure of the P\_PCI information included in the P\_PCI packet. The P\_PCI information includes P\_PCI general information, P\_PCI highlight information, and P\_PCI recording information. The P\_PCI general information includes a P\_VOBU type (P\_VOBU\_CAT) describing the type of the analog copy protection with respect to the P\_VOBU video data, P\_VOBU start time (P\_VOBU\_S\_PTM) describing the PTS of the first video to be displayed included in the P\_VOBU, P\_VOBU termination time (P\_VOBU\_E\_PTM) describing the PTS of the final video to be displayed included in the P\_VOBU, P\_VOBU\_SEQ time (P\_VOBU\_SEQ\_E\_PTM) describing the PTS including the SEQ existing in the P\_VOBU, and P\_VOBU cell reproduction time (P\_VOBU\_C\_ELTM) indicating relative time in a picture cell of the first video to be displayed of the P\_VOBU. The P\_VOB is always an I picture of 1 VOB, 1 cell and 1 video frame, and always includes SEQ. Accordingly, the P\_VOBU\_S\_PTM, P\_VOBU\_E\_PTM, P\_VOBU\_SEQ\_E\_PTM have an identical value, and the P\_VOBU\_C\_ELTM indicates 0.

[0137] The P\_PCI highlight information includes P\_PCI highlight general information (P\_PCI\_HL\_GI) describing the start time, termination time, number of buttons, the initial selection button number, forcible execution button number and the like of the highlight information; a P\_PCI button color information table (P\_BTN\_COLIT) describing button color information; and a P\_PCI button information table (P\_BTNIT) describing the coordinate, magnitude, operation mode and the like of the button. Since the P\_VOBU includes one video frame as described above, the P\_PCI\_HL\_GI is described so that the start time of the highlight information indicates 0 and the termination time indicates infinity.

[0138] The P\_PCI recording information includes a P\_PCI video ISRC code (P\_ISRC\_V) describing an ISRC code of the video of the P\_VOBU; and a P\_PCI

sub-picture ISRC code (P\_ISRC\_SP) describing an ISRC code of the sub-picture of the P\_VOBU.

[0139] Figure 42 shows a structure of the P\_DSI information described in the P\_DSI packet. The P\_DSI includes only the P\_DSI general information (P\_DSI\_GI). The P\_DSI general information includes P\_VOBU\_NV pack time (P\_NV\_PCK\_SCR) corresponding to the least significant 32 bits of the SCR of the NV pack of the P\_VOBU, a P\_VOBU termination address describing the relative address with respect to the NV pack of the final pack of the P\_VOBU, and a P\_VOBU first reference address (P\_VOBU\_1STREF\_EA) describing the relative address with respect to the NV pack of the pack including the final data of the first I picture of the video of the P\_VOBU. Since the P\_VOBU includes 1 VOB, the P\_NV\_PCK\_SCR is always 0.

[0140] Figure 29 shows the relationship among the PGC, audio program, cell, picture program, picture cell, AOB, and P\_VOB. The entirety of Figure 29 represents one PGC. A plurality of such PGCs are included in one ATS. As described above, a PGC includes audio programs describing the reproduction order by the audio data access unit and picture programs describing the reproduction order by the video data access unit. Each audio program has a cell, which is the minimum management unit. The cell points to an AOB which is actual audio data and thus determines the reproduction data. In a similar manner, each picture program has a picture cell, which points to a P\_VOB, which is actual video data, and determines the contents to be reproduced.

[0141] Due to such a structure, actual reproduction data pieces can be recorded on the disk in a different order. Alternatively, the same data piece can be pointed by a plurality of cells or picture cells. In order to guarantee the reproduction continuity, the audio data pieces has a flag which indicates whether the physical layout of the data on the disk is continuous or the data is a continuous part of one AOB (i.e., audio program physical allocation information, audio program time attribute information). The video data is fundamentally a still picture. Accordingly, one video data program includes one cell, and one cell includes one P\_VOB. The physical arrangement of the P\_VOBS causes no specific problems. Thus, the video data does not have such a flag.

[0142] Figure 30 shows an exemplary PGC forming a title. The example shown in Figure 30 includes five programs. Programs #1 and #2 correspond to AOB #1, and programs #3, #4 and #5 correspond to AOB #2. On the recording medium, AOB #1 is recorded after AOB #2. Programs #1 and #2 both include a silent cell and a silent cell, and program #2 includes two audio cells. Programs #3 and #4 include a silent cell, and program #5 includes only an audio cell.

[0143] In the case where all the audio cells each have a reproduction time period of 60 seconds (5,400,000 in PTS) and all the still picture cells each have a reproduction time period of 1 second (90,000 in PTS), audio pro-

gram information can be described as shown in Figure 32. Picture program information can be described as shown in Figure 33. Under the conditions that the audio data is 48 kHz, 16 bit sampling with 2 channels, the number of the silent packs is 96 and the number of the audio cell packs is 5760 as shown in Figure 34. Where the number of still picture packs is 50, the picture cell information is as shown in Figure 35. In such a case, it is assumed that the P\_VOB used in the picture cell is recorded at a position following an AOB. The recording positions for the P\_VOB and AOB are not physically limited, and the P\_VOB and AOB can be positioned in a mixed state with no specific problem. In such a case, the physical allocation of the audio program information of no-Continue indicates that the AOB indicated by the audio program is not continuously reproducible. The audio cell and the picture cell both share the AOBs and P\_VOBS used by the other cells.

[0144] The audio title set has been described. Next, with reference to Figure 22, the audio manager will be described.

### (3.2) Data structure of the audio manager 900

[0145] The audio manager 900 is information for controlling the reproduction which is to be first referred to for performing audio-oriented reproduction of the information on the optical disk by a reproduction apparatus.

[0146] Figure 22 shows a data structure of the audio manager 900.

[0147] The audio manager 900 includes "audio manager information (AMGI)", "VOB for audio manager menu (AMGM\_VOBS)", and "audio manager information backup (AMGI\_BUP)" as in the first example.

[0148] The "audio manager information (AMGI)" includes "audio manager information management table (AMGI\_MAT)" including attribute information and pointer information, "audio title management information" indicating the number of audio titles and the like, "audio title search pointer (ATT\_SRP)" indicating search information on the audio titles, and "audio manager menu PGC management information table (AMGM\_PGCI\_UT)" indicating PGC information for audio manager menu, as in the first example.

[0149] The "audio manager information management table (AMGI\_MAT)" includes an AMG identifier (AMG\_ID) for identifying an audio manager, an AMG termination address (AMG\_EA) which is a termination address for table management, an AMGI termination address (AMGI\_EA), an AMGI\_MAT termination address (AMGI\_MAT\_EA), address information on the AMG and AMGI tables, version number (VERN), a volume set identifier (VLMS\_ID), a number of title sets (TS\_Ns) indicating the number of the title sets included in the volume, a provider identifier (PRV\_ID) for identifying the provider which produced the disk, an automatic execution flag (Auto\_Play\_Flag) defining the operation of the player when the disk is inserted, and

AMGM\_VOBS indicating VOB attribute information existing in the audio manager.

[0150] The "audio title search pointer table (ATT\_SRP)" has an identical structure with that in the first example.

[0151] The audio zone region and the DVD as a multimedia optical disk have been described. Next, a reproduction apparatus, according to the present invention, for reproducing a media having the above-described structure will be described.

[0152] The basic structure of the reproduction apparatus is similar to the structure described in the first example. In the second example, a key for separately controlling audio data and video data is provided in a remote controller for operating the DVD player or a front panel of the DVD player. With such a key, the video data can be skipped forward and backward or rewound to the start of the video data while continuously reproducing the audio data.

[0153] Figure 26 is a block diagram illustrating an internal structure of a DVD player 80 in the second example. The DVD player 80 is different from the DVD player 70 shown in Figure 8 in the structure of the AV decoder section, which will be described below.

[0154] In the second example, there are two streams, which are an AOB as audio data and P\_VOB as video data. An AV decoder section 85a includes two decoders respectively corresponding to the AOB and P\_VOB. These decoders are operated synchronously with or asynchronously from each other. Specifically, the AV decoder section 85a includes a P\_VOB system decoder 103 for receiving a P\_VOB stream and distinguishing a stream ID and sub-stream ID in a header of each packet included in the stream, thereby classifying the data into a video packet, a PCI packet, and a sub-picture packet. The AV decoder section 85a further includes an AOB system decoder 104 for receiving an AOB stream and classifying the data on a packet header-by-packet header basis. The AV decoder section 85a still further includes a highlight buffer 94 for temporarily storing highlight information of a PCI packet from the P\_VOB system decoder 103, a video buffer 96 for temporarily storing a video packet in a similar manner, a sub-picture buffer 105 for temporarily storing a sub-picture packet, an audio buffer 99 for temporarily storing an audio packet from the AOB system decoder 104, a highlight decoder 95 for decoding the highlight information from the highlight buffer 94 and outputting the decoded highlight information to the system control section 93, a video decoder 87 for decoding the video data from the video buffer 96, a sub-picture decoder 98 for decoding the sub-picture data from the sub-picture buffer 105, an audio decoder 100 for decoding the audio data from the audio buffer 99 and outputting the decoded audio data as an audio output, a video synthesizer 101 for synthesizing the decoding results of the video decoder 87 and the sub-picture decoder 98 into one piece of video data, and a synchronization adjusting section 102 for managing

ing the synchronization of the highlight decoder 95, the video decoder 87, the sub-picture decoder 98 and the audio decoder 100.

[0155] The reproduction apparatus according to the present invention operates in, for example, the following manner. The operation up to the reading of the stream is the same as described in the first example and will not be described below.

[0156] For starting the reproduction, the system control section 93 determines whether or not the DVD player 80 is in a video-oriented reproduction mode, by a reproduction mode determination section. When it is determined that the DVD player 80 is in the video-oriented reproduction mode, the system control section 93 reads the video manager based on the information which is read from the volume file management region. The system control section 93 refers to the PGC management information table for the video manager menu to calculate the recording address of the PGC for the volume menu. The resultant PGC is reproduced and retained inside. When the PGC for the volume menu is retained inside, the system control section 93 refers to the retained PGC information to calculate the video object (VOB) to be reproduced and the recording address of the VOB on the optical disk. When the VOB to be reproduced is determined, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to retrieve the determined VOB from the optical disk for reproduction. Thus, the video menu from which the user can select the title to be reproduced is displayed (see Figure 40).

[0157] The user sees the menu and selects and confirms the title that he/she is interested in by designating the item number in the menu using the remote controller. Then, the system control section 93 receives the designation of the item number in the menu from the remote controller and refers to the management information pack included in the VOB of the video menu which is being reproduced, the VOB being input from the AV decoder section 85a, to execute a control command corresponding to the designated number. The control command is PlayTitle #n or the like, and the title number to be reproduced is designated by "n". As an execution operation by the PlayTitle command, the system control section 93 refers to the title search pointer table, which is a part of the audio manager, to determine the audio title set (ATS) to which the designated title belongs to and the title number in the ATS. When the ATS is confirmed, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to reproduce the ATS management information of the confirmed title set and retrieves the title search pointer table of the ATS, which is a part of the ATS management information, to the system control section 93. When the title search pointer table is retrieved, the system control section 93 refers to the table to determine the PGC information

for starting the reproduction of the title to be reproduced. When the PGC information is determined, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to reproduce the determined PGC information and retain the information in the inside buffer memory for the PGC information. When the PGC information is retained, the system control section 93 first refers to the ATS picture program information table, with reference to the retained PGC information, to read all the P\_VOBS described in the PGC information and inputs the P\_VOBS to the AV decoder section 85a. The AV decoder section 85a separates the input P\_VOBS on a pack-by-pack basis or packet-by-packet basis by the P\_VOB system decoder 103 and stores the P\_VOBS in corresponding buffer memories.

[0158] At this point, the highlight decoder 95, the video decoder 87, and the sub-picture decoder 98 do not perform decoding operations. When all the P\_VOBS are stored in the corresponding buffer memories, the AOB to be reproduced and the recording address thereof are determined by the ATS program information table and the ATS cell reproduction information table. Then, the AOB is reproduced by a control signal output to the mechanism control section 83 and the signal processing section 84 from the system control section 93. At this point, the highlight decoder 95, the video decoder 87, and the sub-picture decoder 98 perform decoding operations for the first time to start video output, highlight processing and audio output. The output timing is adjusting by the synchronization adjusting section 102 in accordance with the audio program information, picture program information, highlight information and time code information (PTS) of each packet.

[0159] In the second example, data for the corresponding picture programs is all stored in the corresponding buffers before the audio data is reproduced. Accordingly, the highlight buffer 94, the video buffer 96, and the sub-picture buffer 105 in the DVD player 80 in the second example require a larger buffer memory capacity than the capacity specified by MPEG2 or DVD-Video.

[0160] Thereafter, the system control section 93 sequentially determines the AOBs to be reproduced and controls the reproduction thereof in accordance with the retained PGC information, and also decodes the highlight information, sub-picture information and video information which are already read in the buffer memories. When the reproduction of the final AOB indicated by the PGC information is completed, the system control section 93 searches for the PGC information of the next title and reproduces the P\_VOBS and the AOBs described in the PGC information in the same manner.

[0161] Thus, all the titles are reproduced and the operation is stopped. In accordance with specific setting of the DVD player or the DVD, only one title can be reproduced before the operation is stopped, or a menu



can be displayed after reproduction of one or more titles is completed.

[0162] Next, a method for reproducing a still picture cell, a silent cell and an audio cell will be described in detail.

[0163] Figure 14 shows a conventional method for reproducing the audio cell. Conventionally, for reproducing an MPEG2 stream, the leading end of the audio cell pack is first sought by the optical head and data reading starts. However, audio output does not immediately start but starts after an idle time period, which is predetermined in each reproduction apparatus. The idle time period includes a time period required for determining the PTS of the audio data, a time period required for determining that data is correct, and a time period required for the muting circuit in an analog output section is to be transitioned from a mute state to a non-mute state. Thus, the idle time period varies in accordance with the type of reproduction apparatus. Especially when the reproduction section and the decoder are accommodated in separate chassis, the idle time period tends to be extended because determination on the PTS and the determination on the correctness of the audio data are separately performed.

[0164] Figures 36A and 36B show methods for reproducing a silent cell and an audio cell. Figure 36A shows the method in the case where the reproduction is performed from the leading end of the data, and Figure 36B shows the method in the case where the reproduction is performed in continuation from the previous cell.

[0165] In the case where reproduction is performed from the leading end of the data by selecting a title or program from the menu or the like through jumping, the leading pack of the silent cell is jumped to with reference to the start address of the cell information. At this point, the STC, which is the reference time of the decoder, is set with the SCR of the leading pack of the silent cell. Next, skipping and jumping of data corresponding to a prescribed idle time period are performed with reference to the PTS of the silent cell, and the silent cell for the idle time period is reproduced. Audio output is prepared for during this period. At this point, the next title number is not displayed on the display device of the reproduction apparatus, and the passage of reproduction time period is not updated. In the case where the audio output is started and display of the title number and the updating of the passage of the reproduction time period are performed simultaneously when the first PTS of the leading cell is detected, the reproduction apparatus behaves as if the audio data is output simultaneously with the completion of the jump such as menu selection.

[0166] In the case where the reproduction is performed in continuation from the previous cell, a silent cell is jumped over or skipped except for the idle time period. At this point, by continuously counting the STC, which is reference for the system time, the interval between the completion of the audio output by the pre-

vious cell and the start of the audio output by the next cell equals the audio pause time period. The counting of the STC is continued when the physical allocation information and the time attribute information both have a value indicating "continue". When either one of them indicates "no-continue", the same processing as in the jump from the menu is performed, and thus the STC is reset at the leading end of the silent cell pack. In the case where there is no silent cell and the reproduction starts from the leading end of the data, the operation is similar to the conventional operation shown in Figure 14. In the case where the reproduction is performed in continuation from the previous cell, the operation is as follows. When the time attribute information indicates "continue", the audio cell is decoded continuously from the previous cell and audio data is output. When the time attribute information indicates "no-continue", the operation is the same as the conventional operation shown in Figure 14 as in the case where the reproduction is performed from the leading end of the data.

[0167] Figures 37 through 39 are flowcharts each illustrating a program. Since information on the P\_VOBS is read in the corresponding buffer memories, reproduction of the audio data and processing of the highlight information can be performed asynchronously from each other, and the still picture and the sub-picture can be output asynchronously from each other. Needless to say, synchronous display is possible based on the time code or the time information of the system.

[0168] Regarding reproduction of audio information, in the case where the physical allocation information of the audio program information shows "continue" and the program previously reproduced has a program number which is smaller by one than the program number of the program to be reproduced now- seek to the reading head for the DVD is not specifically necessary. When the time attribute information indicates "continue" and the reproduction is performed in continuation from the previous program, the STC, which is the reference time for the decoder, does not need to be reset.

[0169] The determination of whether or not the cell is a silent cell is performed using the cell type in the cell information. The determination that the cell is the final cell is performed by comparing the termination address of the cell information and the address read from the data in the DVD. The completion of the reproduction of the audio program can be determined by the cell index of the cell information returning to zero, the cell type indicating a still picture cell or a silent cell, or the start cell number of the next program in the audio program information.

[0170] The skipping of the silent cell is performed while detecting the PTS when the silent cell is decoded or by obtaining the number of packs to be skipped based on the data rate.

[0171] Since data of a still picture is already stored in the buffer memory, the display of the still picture is managed based on the position in the buffer memory at



which the still picture of the designated cell of the designated program is recorded or based on the ordinal number (i.e., first, second, etc.) of the still picture with respect to the start. When the management is performed based on the position in the buffer memory, the data is sent to the video decoder 87 from the designated address in the video buffer 96 and displayed. When the management is performed based on the ordinal number of the still picture, the data stored in the video buffer 96 from the leading end thereof is sent to the video decoder 87 and the display is switched when the designated ordinal number is reached. The transmission of the data is stopped at this point. The display time period of the still picture is in accordance with the description in the picture cell still time (P\_C\_Still\_Time). Since still pictures are each 1-frame data, the present still picture is switched into the next still picture when the time period described in the picture cell still time has passed. Such control is usually performed by the system control section 93. A picture cell still time of FFh indicates infinity, which means that the still picture is switched basically only by a command, user operations, or completion of the audio program. When the still picture is switched, display effects can be added by designating the transition mode. The time to switch the still picture can be designated on a program-by-program basis before and after the display of the still picture. However, in the case where the reproduction apparatus does not have a special effect display function, the still picture can simply be switched with the display effects being ignored.

[0172] In a synchronous mode, the audio data is reproduced based on the audio program reproduction time period and the time code information of the audio data, and the still picture and the sub-picture are reproduced based on the picture program reproduction time period. The synchronisation adjusting section 102 compares the reference time information of the system and the reproduction time periods and thus performs synchronization control.

[0173] In an asynchronous mode, audio data is not synchronized with and reproduced separately from highlight data, sub-picture data and still picture data. The highlight data, sub-picture data and still picture data are synchronized to one another, and the audio data is continuously reproduced realtime based on the time information of the system. The still picture is switched in the asynchronous mode by the user operations and the command. The user operations basically include an operation of continuously reproducing audio programs while feeding picture programs forward, backward or to the leading end; and an operation of feeding both audio programs and picture programs simultaneously forward, backward or to the leading end. The command has similar functions.

[0174] The synchronous mode and the asynchronous mode are switched over in accordance with the picture program reproduction control. In the case where the picture program reproduction control is designated so as to

prohibit control by the user operations, the data is basically reproduced in the synchronous mode except for by the command.

[0175] In the case where the picture program reproduction mode prevents the user operations and command from synchronizing audio programs and picture programs with each other, the DVD player can wait until the synchronisation is obtained or the picture programs can be continuously reproduced in accordance with the picture program reproduction time period without synchronization. In the case where the reproduction of the audio programs is not completed when the reproduction of the picture programs is completed, the picture programs can be continuously reproduced from the first picture program or the final picture program can be continuously reproduced. In the case where the reproduction of all the picture programs are completed before all the audio programs are completed, only the picture programs can be reproduced with the audio part being silent, the audio programs can be reproduced from the first audio programs, or the reproduction of the audio title can be terminated. Some of the audio programs and the picture programs included in the audio title can be randomly selected and repeated a designated number of times. Such audio and picture programs can be repeated so that no same program is repeated (shuffle mode). The audio programs and the picture programs are synchronized to each other so that the audio program and the picture program having the same number can be always reproduced simultaneously, or the audio programs and the picture programs can be reproduced independently and asynchronously.

[0176] An audio title number or time can be directly designated for reproduction by user operations, i.e., usually by a remote controller or other keys. Such reproduction by direct designation by user operations cannot be used when the directly designated reproduction prohibition flag (UOP1) and the time designated reproduction prohibition flag (UOP2) of the ATT\_CAT indicate prohibition. By such a designation, the title creators can describe reproducible audio titles by a command under some conditions of the reproduction apparatus. For example, an audio title which is not usually reproducible can be reproduced under certain conditions. For example, a certain parameter can be set in a specific players so that the parameter can be evaluated by a command, and the command can be described so as to reproduce the audio title only when a value is set in the parameter. When UOP1 and UOP2 are set so as to prohibit directly designated reproduction, the audio title can be reproduced only by the specific player. Such a system easily allows reproduction of certain audio titles, recorded on a disk including a plurality of audio titles, for which fee has been paid.

[0177] AV decoder sections having other structures are usable. For example, as shown in Figure 27, an AV decoder section 85b also acts as a system decoder for AOB and P\_VOB. Since the AOB and P\_VOB are input

at different timing, the same type of AV decoder section as used by DVD-Video is usable except that the capacities of the highlight buffer 94, the video buffer 96, and the sub-picture buffer 105 are increased and that a still picture management mechanism is added to the control of the video buffer 96. The operation of the AV decoder section 85b is substantially the same as that of the AV decoder section 85a.

[0178] The DVD player can have the structure shown in Figure 28. In this structure, a P\_VOB buffer 106 for P\_VOB streams is provided immediately before the AV decoder section 85b. The same type of AV decoder section as used by DVD-Video is usable. All the P\_VOB data to be read before the reproduction of the audio data is stored in the P\_VOB buffer 106. The P\_VOB buffer 106 dynamically multiplexes the P\_VOBS corresponding to the reproduction order with the audio stream and sends the resultant data to the AV decoder section 85b. Accordingly, the system decoder 120 for AOB and P\_VOB in the AV decoder section 85b is required to have a processing speed which is slightly higher than the speed specified by the DVD-Video standards. Streams need to be supplied to the AV decoder section 85b so that the audio buffer 99 does not underflow.

[0179] In the second example, as described above, program reproduction information including the start time and reproduction time period of each piece of audio data based on the reproduction start time of the leading audio data in the MPEG2 stream is recorded in the management region as a part of the reproduction control information. Accordingly, an optical disk for realizing reproduction of high quality digital audio data along with the video data in a restricted range of bit rates is provided. Moreover, a certain interval between audio reproductions can be maintained even in an inexpensive reproduction apparatus including no video data reproduction function. This allows title creators to create data easily.

[0180] Since a plurality of still pictures, sub-picture and menu can be displayed synchronously with or asynchronously from high quality audio data, a wider variety of displays become available.

#### (Example 3)

[0181] An optical disk, and an apparatus and method for reproducing information from the optical disk in a third example according to the present invention will be described. Identical elements previously discussed in the first example bear identical reference numerals and the descriptions thereof will be omitted.

#### (1) Physical structure of the optical disk

[0182] The physical structure of the optical disk is identical with that described in the first and second examples and thus the description thereof will be omitted.

ted.

#### (2) Logical structure of the optical disk

[0183] The logical structure of the optical disk is identical with that described in the first and second examples and thus the description thereof will be omitted.

#### (3) Data structure of the audio zone region 32c

[0184] Figure 43 shows a data structure of the audio zone region 32c. The audio zone region 32c stores an audio manager 900 and one or more audio title sets 800 as in the first and second examples. The audio zone region 32c further stores an audio still video set 1100.

##### (3.1) Data structure of the audio manager 900

[0185] Figure 44 shows a data structure of the audio manager 900 in the third example. The structure of the audio manager 900 has the same structure as that shown in Figure 4 down to the stage of the audio manager information management table (AMGI\_MAT) 902.

[0186] The audio manager information management table 902 includes an ASVS start address (ASVS\_SA) 904 for storing the position of the audio still video set.

[0187] The structure of the audio manager information management table 902 is the same as that shown in Figure 22 except for the ASVS start address 904.

##### (3.2) Data structure of the audio still video set 1100

[0188] Figure 45 shows a data structure of the audio still video set 1100. The audio still video set 1100 includes a plurality of picture video objects (hereinafter, referred to as "P\_VOBS") 1102, audio still video set management information (ASVSI) 1101 for managing the plurality of P\_VOBS 1102, and audio still video set management information backup (ASVSI\_BUP) 1103. In the following description, the audio still video set will generally be referred to as an "ASVS". The P\_VOBS 1102 will generally be referred to as an "audio still video object (ASVOB)".

##### (3.2.1) Data structure of the P\_VOB 1102

[0189] Figure 46 shows a data structure of the P\_VOB 1102. The P\_VOB 1102 includes a picture NV pack (P\_NV\_PCK) 1113, a plurality of video packs (V\_PCK) 1114, and a plurality of sub-picture packs (SP\_PCK) 1115. Only one picture NV pack 1113 is included in each P\_VOB 1102.

[0190] The video packs (V\_PCK) 1114 each stores video data forming an MPEG-system I picture. Unlike the VOB, the P\_VOB is for storing a still picture but not a moving picture. Accordingly, the video data stored in each video pack 1114 includes only an I picture which is in-frame-compressed. Herein, information indicating

one still picture corresponds to one I picture.

[0191] The sub-picture packs 1115 can each store a plurality of sub-picture streams. Each sub-picture packs 1115 stores an identification code for identifying the plurality of sub-picture streams. The sub-picture packs 1115 need not be included in the P\_VOB 1102.

[0192] The picture NV pack 1113 includes a DSI packet (not shown) and a PCI packet (not shown). The DSI packet stores information used for special effects such as fast-forward reproduction. The PCI packet stores highlight information 1120 (Figure 47).

[0193] As shown in Figure 47, the highlight information 1120 includes ASV highlight general information 1121 indicating an effective period, the number of buttons, and the like of highlight; ASV button color information 1122 indicating the display color of the button; and an ASV button information table 1123 indicating a button command and the like.

[0194] Unlike in the case of DVD-Video, the P\_VOB 1102 does not have any audio data.

### (3.2.2) Data structure of the audio still video set management information 1101

[0195] As shown in Figure 45, the audio still video set management information 1101 includes audio still video unit information (ASVUI) 1131 for managing a plurality of still pictures as a group and an audio still video search pointer table (ASV-SRPT) 1132 for managing the recording position of the P\_VOB 1102.

[0196] The audio still video unit information 1131 is information for managing a plurality of P\_VOBS 1102 having the same attribute and continuously recorded on the disk. Such information is a basic unit for reproduction processing.

[0197] The audio still video unit information 1131 includes an "audio still video set ID (ASVS\_ID)"; a "number of audio still video sets (ASVS\_Ns)"; a "P\_VOB start address (P\_VOBS\_SA)" and a "P\_VOB termination address (P\_VOBS\_EA)" indicating the recording position of the P\_VOB; an "ASVU attribute" indicating the ASVU attribute such as, for example, a compression method of the P\_VOB, aspect mode and existence of a button; a "P\_VOB sub-picture palette (P\_VOBS\_SP\_PLT)" for determining the display color of the sub-picture; and "ASVU general information (ASVU\_GI)" corresponding to each ASVU for designating the P\_VOB belonging to each ASVU.

[0198] Each "ASVU general information (ASVU\_GI)" includes a "number of P\_VOB (P\_VOB\_Ns)" indicating the number of P\_VOBS forming the ASVU, and a "start P\_VOB number" indicating which P\_VOBS belong to the ASVU.

[0199] The audio still video search pointer table 1132 stores a plurality of "ASV search pointer (ASV\_SRPT)" indicating the start address of each of the P\_VOBS included in the ASVS.

### (3.3) Data structure of the audio title set 800

[0200] Figure 48 shows a data structure of the audio title set 800 in the third example. The audio title set 800 shown in Figure 48 has the same structure as that shown in Figure 5 except for the structure of the PGC information 833.

[0201] Figure 49 shows a data structure of the PGC information 833. The PGC information 833 includes "ATS PGC general information (ATS\_PGC\_GI)", an "ATS program information table (ATS\_PGIT)", an "audio cell reproduction information table (ATS\_C\_PBIT)", and an "ATS audio still video reproduction information table (ATS\_ASV\_PBIT)".

[0202] The "ATS PGC general information (ATS\_PGC\_GI)" includes the number of audio programs and the number of cells included in the PGC information; the reproduction time period of the PGC; and information the ATS\_PGC information. The address information on the ATS\_PGC information includes pointer information to an "ATS program information table (ATS\_PGIT)", an "audio cell reproduction information table (ATS\_C\_PBIT)", and an "ATS audio still video reproduction information table (ATS\_ASV\_PBIT)".

[0203] The "ATS program information table (ATS\_PGIT)" includes a plurality "audio program information (ATS\_PGI)" units included in the PGC.

[0204] Each of the plurality of "audio program information (ATS\_PGI)" units includes "audio program physical allocation information" indicating whether or not the AOB of each program and the AOB of the previous program are recorded at physically discontinuous positions on the optical disk, "audio program time attribute information" indicating whether or not the time information of the AOB is continuous with the time information of the previous AOB, an "audio program start cell number" indicating the first cell number forming the audio program, "reproduction start audio cell time" indicating the first time information of the first audio cell included in the audio program, an "audio program total reproduction time period" indicating the reproduction time period of the audio program, an "audio pause time period" indicating the silent period until the reproduction of the audio cell of the audio program starts, an "ASVU number (ASVUN)" designating the still picture unit to be reproduced simultaneously with audio data of the program, an "audio still video display mode (ASV\_DMOD)" indicating the display mode of the still picture such as, for example, whether the still picture or still pictures are displayed in accordance with the order or randomly, and an "ATS\_ASV\_PBI start address" and "ATS\_ASV\_PBI termination address" designating corresponding ATS audio still video reproduction information in the ATS audio still video reproduction information table (ATS\_ASV\_PBIT).

[0205] Figure 50 shows a data structure of the "audio still video display mode (ASV\_DMOD)". The "audio still video display mode (ASV\_DMOD)" includes a "display

timing mode" flag and a "display order mode" flag.

[0206] The "display timing mode" indicates specific timing for reproducing the audio data and an updating time period of the still picture.

[0207] When the "display timing mode" is Browsable, the display timing of the still picture can be changed by interaction from the user. When the "display timing mode" is SlideShow, the display timing of the still picture cannot be changed by interaction from the user.

[0208] When the "display timing mode" is SlideShow, the display of the still picture is updated in accordance with the display timing determined synchronously with the audio information which is simultaneously reproduced. When the "display timing mode" is Browsable, the display of the still picture is updated when the determined display continuation time period has passed, asynchronously from the audio information which is simultaneously reproduced.

[0209] The "display order mode" indicates whether the still picture or still pictures are displayed sequentially in accordance with the display list, randomly or shuffle. A random display of the still picture refers to that the still picture or still pictures are selected randomly while permitting overlap and are displayed in conformity with the selected order. A shuffle display of the still picture refers to that the still picture or still pictures are selected randomly while prohibiting overlap and are displayed in conformity with the selected order.

[0210] The "audio cell reproduction information table (ATS\_C\_PBIT)" includes a plurality of "audio cell reproduction information (ATS\_C\_PBI)" units. Each "audio cell reproduction information unit (ATS\_C\_PBI)" includes a "cell index number" indicating the order of cells included in the program, a "cell type" indicating the attribute of the cell (i.e., whether the cell is a still picture cell or a silent cell), a "cell start address" indicating the start address of the cell in the form of a relative address with respect to the first pack of the AOB of the ATS including the cell, and a "cell termination address" indicating the final address of the cell in the same manner.

[0211] The "ATS audio still video reproduction information table (ATS\_ASV\_PBIT)" includes a plurality of "ATS audio still video reproduction information (ATS\_ASV\_PBI)" units. Each "ATS audio still video reproduction information unit (ATS\_ASV\_PBI)" includes a plurality of "display lists (DLIST)" indicating which P\_VOBS stored in the audio still video set are reproduced and in which order the P\_VOBS are reproduced.

[0212] Each "display list (DLIST)" includes an "ASV number" indicating the ordinal number (i.e., first, second or the like) of the P\_VOB in the ASVU, an "initial button number (FOSL\_BTNN)" indicating the number of a button which is in the highlight information and selected in an initial state, an "audio program number" indicating the audio program corresponding to the DLIST, "display timing" indicating the timing for displaying the P\_VOB included in the DLIST, and a "start section transition mode" and a "termination section transition mode" indi-

cating the transition of the still picture.

[0213] In this example, as the picture transition modes, "no transition", "fading from black", "fading into black", "cross-fading", and "wiping in several directions" are assumed.

#### (3.4) Data structure of the AOB 802

[0214] The AOB 802 is packetized into 2 Kbytes. The AOB 802 stores data in the LPCM format, AC3 format, DTS format or other compression formats. In the case of the LPCM format, the sample bit is 16, 20, or 24 bits, with a sampling frequency of 48 kHz, 96 kHz, 192 kHz, 44.1 kHz, 88.2 kHz, or 176.2 kHz.

[0215] The AOB 802 has an exemplary structure as described in the second example with reference to Figure 24.

#### (4) Two reproduction methods

[0216] The audio zone region 32a stores three MPEG streams of a VOB, an AOB and a P\_VOB. The AOB is included in the audio title set (ATS). The P\_VOB is included in the audio still video set (ASVS). The VOB is included in the audio manager (AMG) as shown in Figure 44.

[0217] The AOB and the P\_VOB are the main information stored on the disk, and are typically music information with a still picture. The VOB is typically a menu for allowing the user to select any music information with a still picture.

[0218] Among the MPEG streams stored in the audio zone region 32c, the VOB is reproduced by a standard method specified by MPEG. The AOB and the P\_VOB are reproduced by an expanded different method which is different from the standard method.

#### (4.1) Standard reproduction method

[0219] First, the standard reproduction method will be described. This method is used for reproducing a VOB stored on the optical disk.

[0220] Figure 51 shows a data structure of a system stream in the third example conforming to MPEG. The optical disk stores at least one system stream.

[0221] The system stream can include a plurality of elementary streams. The elementary streams include a video elementary stream storing moving picture information, an audio elementary stream storing audio information, and a sub-picture elementary stream storing sub-picture information. The plurality of elementary streams are each divided into a plurality of packs.

[0222] The system stream shown in Figure 51 includes a video elementary stream, an audio elementary stream, and a sub-picture elementary stream. The video elementary stream is divided into one or more video packs. The audio elementary stream is divided into one or more audio packs. The sub-picture elemen-

tary stream is divided into one or more sub-picture packs. In Figure 51, the letter "V" represents a video pack, the letter "A" represents an audio pack, and the letter "S" represents a sub-picture pack.

[0223] As shown in Figure 51, each pack includes a "pack header", a "packet header" and a "data field". The data length of one pack is 2Kbyte.

[0224] Described in the "pack header" is data conforming to MPEG including, for example, a pack start code, an SCR (System Clock Reference), and an MUX (Multiplex) rate.

[0225] Described in the "packet header" is data conforming to MPEG including, for example, a stream ID, a packet length, an STD (System Target Decoder), a buffer scale size, and a PTS (Presentation Time Stamp).

[0226] The stream ID described in the "packet header" indicates whether data stored in the "data field" is a video elementary stream or any other elementary stream. Any other elementary stream is an audio elementary stream, a sub-picture elementary stream or management information.

[0227] The management information is referred to as an "NV pack". The management information includes a PCI packet and a DSI packet. The PCI packet stores highlight information for receiving and processing user interaction. The DSI packet stores information utilized for special effects such as, for example, fast-forward reproduction.

[0228] In this example, the data field of the elementary streams other than the management information stores a sub-stream ID. The sub-stream ID is an 8-bit field indicating whether the data stored in the data field is audio data or sub-picture data. The sub-stream ID further indicates an encode type and a channel identification number. When the data stored in the data field is audio data, the encode type is one of the linear PCM format, AC-3 format, DTS format and the like, and the channel identification number is one of #0 through #7 (8 types max.). When the data stored in the data field is sub-picture data, the channel identification number is one of #0 through #31 (32 types max.).

[0229] In the "data field", data compressed in accordance with a prescribed format is recorded. For example, video data is compressed by MPEG2 and recorded in the data field. Audio data is compressed by the linear PCM, AC-3 or DTS format and recorded in the data field. Sub-picture data is compressed by the run-length coding and recorded in the data field.

[0230] The PTS in the "pack header" and the "packet header" is used to synchronize the decoding of the audio pack and the decoding the sub-picture pack.

[0231] In the case where the reproduction apparatus reproduces a system stream recorded on the optical disk, the reproduction apparatus sets the SCR included in the leading pack of the system stream as an initial value of the STC, which is a reference clock, and inputs each pack to the corresponding decoder at time timing

indicated by the SCR while referring to the STC. Each of the decoded packs is externally output from the decoder at the timing indicated by the PTS. By outputting each pack at the timing indicated by the PTS included in the pack, the synchronisation of the audio, video and sub-picture outputs is guaranteed.

[0232] As described above, in the case of using the standard reproduction method, the system stream to be reproduced is multiplexed with audio information, video information and sub-picture information. The system streams are reproduced by resetting the STC, which is a reference clock, of each system stream and externally outputting the audio, video and sub-picture data from the decoder at the timing indicated by the PTS included in each pack. Thus, the audio data, video data and sub-picture data are reproduced synchronously with one another.

#### (4.2) Reproduction method of AOB and P\_VOB

[0233] Hereinafter, a reproduction method of an AOB and a P\_VOB recorded on the optical disk will be described.

[0234] Figure 52 shows the relationship among the P\_VOB, ASVU, Program and AOB.

[0235] An ATS can include a plurality of PGC information (ATS\_PGCi) units. In the example shown in Figure 52, the ATS includes one PGC information unit (ATS\_PGC1).

[0236] Described in the PGC information is one or more audio program information (ATS\_PGI) units (e.g., Program #1, Program #2, ... Program #L). The audio program information is an audio data access unit.

[0237] The audio program information includes one or more audio cell reproduction information (ATS\_C\_PBI) units. The audio cell reproduction information unit is a minimum management unit. The audio cell reproduction information points to the position in the audio data stored in the AOB. Thus, the audio data to be reproduced in relation to the audio cell reproduction information is determined.

[0238] Also described in the PGC information is one or more ATS audio still video reproduction information (ATS\_ASV\_PBI) units. The ATS audio still video reproduction information defines the mode in which the still picture is reproduced on a program-by-program basis. A plurality of audio program information units can share one ATS audio still video reproduction information unit. In the example shown in Figure 52, Program #1 and Program #2 share ATS\_ASV\_PBI#1.

[0239] The audio still video reproduction information can be shared when a plurality of audio program information units point to a common entry in the ATS audio still video reproduction information table (ATS\_ASV\_PBIT).

[0240] Figure 69 shows the relationship between the DLIST and P\_VOB.

[0241] The ATS\_ASV\_PBI includes a plurality of dis-

play lists (DLIST), and each DLIST points to the still picture data (P\_VOB) to be displayed. Usually, the still picture data (P\_VOB) is reproduced in accordance with the order of the DLIST. The ATS\_ASV\_PBI can be designated by the unit of the program of the ATS\_PGCI. The same ATS\_ASV\_PBI can be designated by continuous programs. The P\_VOB can be designated by the ASVU, which is a reading unit. The same ASVU is designated by the programs designating the same ATS\_ASV\_PBI.

[0242] In other words, continuous programs can be designated so as to use the same ATS\_ASV\_PBI with respect to the same ASVU. This is referred to as the ASVU range.

[0243] During the reproduction of the programs in the same ASVU range, the same ASVU is used. Accordingly, the still picture is not read and thus the reproduction of audio data is not interrupted. The DLIST of the ATS\_ASV\_PBI can designate an arbitrary P\_VOB which is included in the same ASVU. Accordingly, the same P\_VOB can be designated a plurality of times. The P\_VOB in the ASVU need not be designated in the DLIST.

[0244] Accordingly, different still pictures can be reproduced while using the same ASVU among different programs, although the ATS\_ASV\_PBI needs to be changed.

[0245] The audio program information designates the ASVU recorded in the ASVS in order to designate a plurality of still pictures (P\_VOB) to be displayed simultaneously with the reproduction of the AOB.

[0246] The ASVU defines the unit by which the reproduction apparatus buffers the still picture data. In other words, the still picture data in the designated ASVU is read before one audio program information unit is reproduced. Accordingly, the reproduction apparatus need not read the still picture data from the optical disk while reproducing a music program.

[0247] When reproducing the next music program information, the reproduction apparatus determines whether the plurality of pieces of still picture data indicated by the required ASVU exists in the main memory area or not. In the case where the plurality of pieces of still picture data of ASVU used in the previous audio program information exist in the main memory area, the reproduction apparatus need not read the still picture data from the optical disk.

[0248] The disk title creators can allow the reproduction apparatus to switch from one audio program information unit to the next audio program information unit rapidly by causing one ASVU to be shared by the two audio program information units. The reproduction apparatus can perform rapid switching from one audio program unit into the next audio program unit when the successive audio program units share the ASVU.

[0249] Each ATS\_ASV\_PBI manages the display order of the still pictures to be displayed by the display list (DLIST). In the display list (DLIST), the still picture to

be displayed is designated by the ASV number. The ASV number is used for specifying the still picture included in the ASVU.

[0250] Thus, the PGC information allows the still picture to be designated for each audio program information unit. Alternatively, the same still picture can be displayed for a plurality of audio program information units. Even when the audio program information is changed, the display can be changed without muting the audio data.

[0251] Figure 53 shows an exemplary PGC forming a title. In this example, the PGC includes four audio programs. Audio program #1 corresponds to AOB #1, audio program #2 corresponds to AOB #2, audio programs #3 and #4 correspond to AOB #3. On the recording medium, the AOBs are recorded in the order of AOB#1, AOB#2 and AOB#3. Audio programs #1, #2 and #3 each has a silent cell, and audio programs #2 has two music cells.

[0252] Audio programs #1 and #2 represent ASVU#1, and audio programs #3 and #4 represent ASVU#2. P\_VOB #1 is displayed in the cell #2, P\_VOB #2 is displayed in the cell #4, P\_VOB #3 is displayed in the cell #5, P\_VOB #4 is displayed in the cell #7, and P\_VOB #5 is displayed in the cell #8.

[0253] In the case where all the audio cells each have a reproduction time period of 60 seconds (5,400,000 in PTS) and all the still picture cells each have a reproduction time period of 1 second (90,000 in PTS), audio program information can be described as shown in Figure 54. Still picture program information can be described as shown in Figure 55.

[0254] Under the conditions that the audio data is 48 kHz, 16 bit sampling with 2 channels, the number of the silent packs is 96 and the number of the audio cell packs is 5760 as shown in Figure 56. Where the number of still picture packs is 50, the ASV search pointer is as shown in Figure 57. The ASVU general information is as shown in Figure 58.

[0255] In this example, the address information on the ASV search pointer is a relative address with respect to the recording position of the first P\_VOB, but can be in any other form which specifies the position of the P\_VOB on the optical disk. In the case where, for example, the ASVU generation information includes address information acting as the reference, the address information of the ASV search pointer can be the relative address with respect to the position indicated by the address information in the ASVU general information.

[0256] When the audio still video display mode is "SlideShow" as in the case of programs #1 and #2 shown in Figure 54, the still picture reproduction is reproduced in synchronization with the audio data. Since the ASVU number of the programs #1 and #2 is "1", ASVU #1 is read to the buffer before the reproduction of the programs. Then, as shown in Figure 55, the still picture information #1 is referred to from the address information of the ATS\_ASV\_PBI to start the



display of still pictures in display lists #1, #2 and #3 in the ATS audio still video reproduction information #1 at the time indicated by the "audio program number" and "display timing" of the display lists. The display timing is synchronous with the reproduction time period of the audio information to be reproduced with the still pictures.

[0257] More specifically, the still picture in the display list #1 of the ATS audio still video reproduction information #1 is displayed when the PTS becomes 90,000 while the AOB #1 is being reproduced. The still picture in the display list #2 of the ATS audio still video reproduction information #1 is displayed when the PTS becomes 90,000 while the AOB #2 is being reproduced. The still picture in the display list #3 of the ATS audio still video reproduction information #1 is displayed when the PTS becomes 5,580,000 while the AOB #2 is being reproduced.

[0258] As described above, when the audio still video display mode is "SlideShow", the still picture is displayed at prescribed timing synchronously with the reproduction of the audio data. The display timing cannot be changed by the interaction from the user (e.g., selection of a specific button by the mouse).

[0259] Figure 59A shows the relationship between the reproduction timing of the audio data and the display timing of the still picture when the audio still video display mode is "SlideShow".

[0260] By contrast, when the audio still video display mode is "Browsable" as in the case of programs #3 and #4 shown in Figure 54, the still picture is reproduced asynchronously from the audio data. Since the ASVU number of the programs #3 and #4 is "2", the ASVU #2 is read to the buffer before the reproduction of the programs. Then, still picture information #2 is referred to from the address information of the ATS\_ASV\_PBI. The display timing of the still pictures in display lists #1 and #2 in the ATS audio still video reproduction information #2 can be changed by the interaction from the user (e.g., input of a command by the user).

[0261] In the case where no interaction from the user is generated within the period indicated by the "display timing" of the display list, the time period indicated by the "display timing" is considered as the display continuation time period. When the display continuation time period has passed, the display of the next still picture is started.

[0262] It is possible to designate with the audio still video display mode whether the still pictures are sequentially displayed in accordance with the display list, the still pictures randomly selected while permitting overlap are reproduced (random reproduction), or the still pictures randomly selected while prohibiting overlap are reproduced (shuffle reproduction).

[0263] Practically, when the reproduction starts with program #3, ASVU #2 is loaded to the buffer since the ASVU number of program #3 is "2". Then, the DLIST indicated by the ATS audio still video reproduction infor-

mation #2 is referred to from the address information of the ATS\_ASV\_PBI. Since the audio program number of display list #1 is "3", P\_VOB #4 corresponding to the ASV number of the display list #1 is displayed. When a key corresponding to the Next\_DLIST provided on the remote controller is pressed, the still picture of DLIST #2, i.e., P\_VOB #5 indicated by the ASV number of DLIST #2 is displayed.

[0264] The still pictures in the DLISTS are displayed in accordance with the "display effect" (i.e., the start section display effect and termination section display effect, see Figure 55). When no user operation is performed within the time of 5,490,000 indicated by the display timing of display list #1, i.e., about 1 minute (matching to the reproduction time period of program #3), the still picture of the next DLIST, i.e., P\_VOB #5 is displayed in accordance with the "display effect" and the "transition time". The audio data of program #4 is reproduced in relation with the display of P\_VOB #5.

[0265] In the case where the reproduction time period of program #3 is shorter than the time period indicated by the display timing of P\_VOB #4, the display of P\_VOB #4 is terminated and the display of P\_VOB #5 is started while program #3 is being reproduced. In the case where the display time period indicated by the display timing of P\_VOB #4 is longer than the reproduction time period of program #3, the display of P\_VOB #5 is started after the reproduction of program #4 is started.

[0266] When the reproduction is started with program #4, ASVU #2 is read as in the case of starting with program #3 to display the P\_VOB in the first DLIST having the audio program number of "4". Thereafter, the display of the still pictures can be changed in accordance with the user operations or command. The audio program number of the DLIST is effective only for determining the P\_VOB to be displayed first only when the ASVU is changed. When the reproduction is continued, a user operation or command has priority over the audio program number. When the P\_VOB is displayed while the time period indicated by the display timing, the P\_VOB indicated by the next DLIST is displayed.

[0267] When the value indicated by the display timing refers to "infinity", the corresponding P\_VOB is continuously displayed until the user operation or execution of a command is performed. As the value indicating the infinity, the maximum value (e.g., all the bit values are "1") can be used but other values are also usable. When the audio still video display mode is "Browsable", the display time period of the P\_VOB can always be infinite.

[0268] Figure 59B shows the relationship between the reproduction timing of the audio data and the display timing of the still picture when the audio still video display mode is "Browsable".

[0269] In this example, information required for each audio programs is recorded in the audio program information (ATS\_PGI). When the information is found to correspond to each audio program, the information can be recorded in any area. For example, as shown in Fig-



ure 60, the ASVU number, audio still video display mode, ATS\_ASV\_PBI start address, and ATS\_ASV\_PBI termination address are recorded in the audio still video reproduction information search pointer (ATS\_PG\_ASV\_PBI\_SRP).

[0270] As described above, the AOB and P\_VOB are reproduced simultaneously by decoders unlike in the case of the VOB.

[0271] Hereinafter, the reproduction method of the VOB and the reproduction method of the AOB and P\_VOB will be compared.

[0272] The two reproduction methods are identical with each other in that video information is output along with the audio information. It should be noted that in the case of the P\_VOB, the video information is still picture information including an I picture.

[0273] One difference between the two reproduction methods is the recording position of the data. In the case of the VOB, audio information and video information are multiplexed together and recorded on the optical disk as one system stream, whereas the AOB and the P\_VOB are recorded in different areas of the optical disk as different system streams.

[0274] Another difference between the two reproduction methods is the synchronization method of audio data and still picture data. VOBs are reproduced by a decoder one by one as described above. In more detail, the STC, which is a reference clock, is reset by the SCR in the "pack header", and the STC is referred to output both audio information and still picture information at the timing of the PTS in the "packet header" in each pack. By contrast, AOBs and P\_VOBs are reproduced by decoders simultaneously. As described in more detail below, a plurality of prescribed P\_VOBs to be reproduced synchronously with the AOB are read from the disk and input to the decoder before the AOBs. Unlike the VOBs, the P\_VOBs input to the decoder are not displayed immediately but are held in the decoder. Regarding each P\_VOB, it is considered that the STC is reset with the SCR of the leading pack in accordance with the MPEG decoding model and the P\_VOB is decoded in accordance with the PTS in the packet, so that data after the plurality of prescribed P\_VOBs to be reproduced synchronously with the AOB is accumulated. Actually, the data regarding the P\_VOB before being decoded is accumulated in an appropriate buffer. When the P\_VOBs are completely input into the decoder, the AOB is read from the optical disk and input to the decoder. When the AOB is input to the decoder, the STC, which is a reference clock, is reset by the SCR in the leading pack, and the AOB is output at the timing of the PTS in each pack header referring to the STC as in the case of the VOB.

[0275] Information on the actual output timing of the P\_VOBs is recorded in another area of the optical disk (i.e., DLIST as a part of the PGC information). The information on the output timing is separately supplied to the decoder. Each P\_VOB in the decoder is not output syn-

chronously with the STC but at the display timing recorded in the DLIST. In other words, in reproducing the AOB, the PTS which is included in the AOB is used to determine the display timing of the AOB; and in reproducing the P\_VOB, the information which is separately recorded from the P\_VOB is used to determine the display timing of the P\_VOB.

[0276] The audio zone region and the DVD as a multimedia optical disk have been described. Next, a reproduction apparatus in this example for reproducing a media having the above-described structure will be described.

[0277] The basic structure of the reproduction apparatus in this example is the same as those described in the first and second examples. As in the second example, a key for separately controlling audio data and video data is provided in a remote controller for operating the DVD player or is provided on a front panel of the DVD player. With such a key, the video data can be skipped forward and backward or rewound to the start of the video data while continuously reproducing the audio data.

[0278] Figure 61 is a block diagram illustrating an internal structure of a DVD player 90 in the third example. The DVD player 90 is different from the DVD player 70 shown in Figure 8 in the structure of the AV decoder section, which will be described below.

[0279] In the third example, usable streams include an AOB as audio data, and a P\_VOB as video data, and a VOB for menu or the like obtained by multiplexing audio and video data. An AV decoder section 85c includes a P\_VOB system decoder 103, an AOB system decoder 104, and a VOB system decoder 108. The AV decoder section 85c has a structure to operate the system decoders 103, 104 and 108 synchronously with and asynchronously from one another.

[0280] The P\_VOB system decoder 103 receives a P\_VOB stream and distinguishes a stream ID and sub-stream ID in a header of each packet included in the stream, thereby classifying the data into a video packet, a PCI (highlight) packet, and a sub-picture packet.

[0281] The AOB system decoder 104 receives an AOB stream and classifies the data on a packet header-by-packet header basis.

[0282] The VOB system decoder 108 receives a VOB stream and distinguishes a stream ID and sub-stream ID in a header of each packet included in the stream, thereby classifying the data into an audio packet, a video packet, a PCI (highlight) packet, and a sub-picture packet.

[0283] The AV decoder section 85c still includes a highlight buffer 94 for temporarily storing highlight information of a PCI packet from the P\_VOB system decoder 103 and the VOB system decoder 108, a video buffer 96 for temporarily storing a video packet from the P\_VOB system decoder 103 and the VOB system decoder 108, a sub-picture buffer 105 for temporarily storing a sub-picture packet from the P\_VOB system

decoder 103 and the VOB system decoder 108, an audio buffer 99 for temporarily storing an audio packet from the AOB system decoder 104 and the VOB system decoder 108, a highlight decoder 95 for decoding the highlight data from the highlight buffer 94 and outputting the decoded highlight data to the system control section 93, a video decoder 87 for decoding the video data from the video buffer 96, a sub-picture decoder 98 for decoding the sub-picture data from the sub-picture buffer 105, an audio decoder 100 for decoding the audio data from the audio buffer 99 and outputting the decoded audio data as an audio output, a video synthesizer 101 for synthesizing the decoding results of the video decoder 87 and the sub-picture decoder 98 into one piece of video data, and a synchronization adjusting section 102 for managing the synchronization of the highlight decoder 95, the video decoder 87, the sub-picture decoder 98 and the audio decoder 100.

[0284] The reproduction apparatus having the above-described structure operates in, for example, the following manner. The operation up to the reading of the stream is the same as described in the first and second examples and will not be described below.

[0285] Figures 62 through 66 are schematic flowcharts illustrating an operation for reproducing the PGC information.

[0286] For starting the reproduction, the system control section 93 determines whether or not the DVD player 90 is in a video-oriented reproduction mode, by a reproduction mode determination section. When it is determined that the DVD player 90 is in the video-oriented reproduction mode, the system control section 93 reads the video manager based on the information which is read from the volume file management region. The system control section 93 refers to the PGC management information table for the video manager menu to calculate the recording address of the PGC for the volume menu. The resultant PGC is reproduced and retained inside. When the PGC for the volume menu is retained inside, the system control section 93 refers to the retained PGC information to calculate the video object (VOB) to be reproduced and the recording address of the VOB on the optical disk. When the VOB to be reproduced is determined, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to retrieve the determined VOB from the optical disk for reproduction. When the system stream forming the VOB is input to the AV decoder section 85c, an instruction indicating "reproduce VOB" as a decode stream instruction is given to the AV decoder section 85c.

[0287] The VOB input to the AV decoder section 85c is divided into streams forming the VOB, i.e., an audio pack, video pack, sub-picture pack, and NV pack by the VOB system decoder 108, and the streams are respectively input to the audio buffer 99, the video buffer 96, the sub-picture buffer 105, and the highlight buffer 94. The highlight buffer 95 buffers only the highlight infor-

mation in the PCI packet in the NV pack. Data input to each buffer is input to the audio decoder 100, the video decoder 87, the sub-picture decoder 98 or the highlight decoder 95 to be decoded. Audio data for menu is output from the audio decoder 100. The outputs from the video decoder 87 and the sub-picture decoder 98 are synthesized by the video synthesizer 101 and output as video data. The output from the highlight decoder 95 is read to the system control section 93 and the button information or the like of each menu is stored in the memory in the system control section 93.

[0288] Thus, a video menu from which the user can select the title to be reproduced (i.e., audio program) is displayed (see Figure 40).

[0289] The user sees the menu and selects and confirms the title that he/she is interested in by designating the item number in the menu using the remote controller. Then, the system control section 93 receives the designation of the item number in the menu from the remote controller and refers to the button information of the highlight information of the PCI pack included in the VOB of the video menu which is being reproduced, the VOB being stored in the memory, to execute a control command corresponding to the designated number. The control command is PlayProgram #n or the like, and the title number to be reproduced is designated by "n".

[0290] As an execution operation by the PlayProgram command, the system control section 93 refers to the title search pointer table, which is a part of the audio manager, to determine the audio title set (ATS) to which the designated title belongs to and the title number in the ATS. When the ATS is confirmed, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to reproduce the ATS management information of the confirmed title set and sequentially retrieves ATS PGC information search pointer, which is a part of the ATS management information, to determine the PGC information including the audio program to be reproduced.

[0291] When the PGC information is determined, the system control section 93 outputs a control signal to the mechanism control section 83 and the signal processing section 84 so as to reproduce the determined PGC information from the disk and retain the information in the inside buffer memory for the PGC information.

[0292] When the PGC information is retained, the system control section 93 reproduces the PGC information in accordance with the flowchart shown in Figure 62. It is assumed that the audio program to be produced is already determined by the above-described menu command or direction designation using the remote controller. The system control section 93 refers to the retained PGC information to first acquire the ASVU number of the first audio program information and compares the number with the ASVU number previously reproduced. When the ASVU number is changed, the system control section 93 reads all the still picture data, i.e., P\_VOBS

included in the ASVU based on the ASVU general information corresponding to the ASVU number and inputs the number into the AV decoder section 85c. Simultaneously, an instruction indicating "reproduce P\_VOB" is given to the AV decoder section 85c as a decode stream instruction from the system control section 93. The AV decoder section 85c separates the input P\_VOBs on a pack-by-pack basis or packet-by-packet basis by the P\_VOB system decoder 92 and stores the P\_VOBs in corresponding buffer memories.

[0293] At this point, the size of the video buffer 96 needs to be larger than the sum of the sizes of the P\_VOBs of the ASVU. For any reproduction apparatus, a maximum value of the total data amount of the P\_VOBs included in the ASVU is set in order to guarantee the reproduction. The video buffer 96 in any reproduction apparatus needs to have a size accommodating the maximum value. In this example, the maximum value of 2 MByte. Since an I picture is 100 to 200 Kbyte, 10 to 20 I pictures can be reproduced along with the audio information.

[0294] When all the P\_VOBs forming the ASVU are completely input to the decoder, the highlight decoder 95, the video decoder 87, and the sub-picture decoder 98 do not perform a decoding operation. In order to store all the data regarding the corresponding ASVU into the buffers before the audio data is reproduced, the highlight buffer 94, the video buffer 96, and the sub-picture buffer 105 need to have a greater buffer capacity than the buffer capacity specified by MPEG2 or DVD-Video.

[0295] When all the P\_VOBs are completely stored in the corresponding buffers, the AV decoder section 85c and the audio decoder 100 are set to be in a decodable state by the audio encoding mode in the ATS PGC information search pointer 832 corresponding to the designated PGC information for preparation of the reproduction of the audio data of the designated PGC. Then, the system control section 93 prepares for the display of the still picture. The system control section 93 determines the ATS audio still video reproduction information from the ATS\_ASV\_PBI start address of the audio program information.

[0296] When the audio still video display mode of the audio program information is Browsable, the first DLIST of the ATS audio still video reproduction information determines the first still picture to be reproduced. When the audio still video display mode is SlideShow, the DLIST having the earliest display timing among a plurality of DLISTS of the ATS audio still video reproduction information in the range of audio programs to be reproduced is selected. When the DLIST is determined, the system control section 93 displays the still picture, i.e., the P\_VOB designated by the ASV number of the DLIST. Specifically, the system control section 93 outputs display control information of the still picture information to the synchronization adjusting section 102 in the AV decoder section 85c. The display control information

includes a wait period until the I picture of the P\_VOB to be updated is designated and the update thereof is displayed. When the display control section is input, the synchronization adjusting section 102 instructs the video decoder 87 to output the designated I picture at the designated timing in accordance with the display control information. Thus, the P\_VOB is displayed. Unlike the AOB and VOB, the P\_VOB is output at the display timing recorded in a separate area.

[0297] When the display of the P\_VOB is started, the audio data designated by the audio program is reproduced simultaneously. Simultaneously, the key operation by the user is accepted.

[0298] The reproduction of the audio data designated by the audio program is performed as shown in Figure 63. First, the cell number (Cn) to be reproduced is determined by the ATS program information table and the ATS cell reproduction information table. Here, since this is the start of the operation, the cell number is 1. When the cell type of the cell to be reproduced is a silent cell, processing for reproducing a silent cell is performed. This requires only the effective silent period corresponding to the reproduction time period of the silent cell. When the cell is not a silent cell, the cell is an audio cell. Accordingly, the reproduction of the audio cell shown in Figure 65 is performed. In order to output the audio data from the leading end of the audio cell, the AOB to be reproduced and the recording address thereof are determined based on the audio cell reproduction information, and a control signal is output to the mechanical control section 83 and to a signal processing section 84. Thus, the reproduction of the determined AOB is prepared. The AOB read from the optical disk is input to the AV decoder section 85c. Simultaneously, the system control section 93 gives an instruction indicating "reproduce AOB" as a decode stream instruction to the AV decoder section 85c. The AOB is decoded into an audio stream by the AOB system decoder 104 and input to the audio buffer 99 and then to the audio decoder 100. Thus, the AOB is prepared to be output as audio data. Once the AOB is prepared, the STC, which is a reference clock, of the synchronization adjusting section 102 is reset by the SCR of the leading pack of the AOB, and the audio data in the AOB is output at the timing of the PTS stored in the packet header. When the output of the AOB is started, highlight information and sub-picture information for the leading I picture of the P\_VOB and the menu items displayed in the state of overlapping with the leading I picture are decoded and output. Although it is not guaranteed that all the packets of the AOB include a PTS, the audio decoder outputs the audio data while complementing the PTS.

[0299] When the audio still video display mode is Browsable while the audio data is being output and the display timing of DLIST corresponding to the P\_VOB which is being displayed reaches the PTS of the audio data which is being reproduced, it is determined that the display time period of the still picture has passed and

thus the still picture of the next DLIST is reproduced. When the audio still video display mode of the audio program is SlideShow and the audio program number of the next DLIST is not the same as the audio program number of the DLIST which is being reproduced, it is determined that there is no DLIST to be reproduced and thus the still picture displayed is continuously displayed. When the next DLIST is the same as the audio program number of the DLIST which is being reproduced, the still picture of the next DLIST is reproduced when the display timing of the next DLIST reaches the PTS of the audio data which is being reproduced.

[0300] Figure 66 is a flowchart illustrating the reproduction of the second and later still pictures. First, the termination transition mode of the DLIST of the still picture which is being displayed is acquired. When the termination transition mode is "no transition", the display is terminated. When the termination transition mode is not "no transition", i.e., when the transition effect is designated, the still picture is erased by the designated transition. The designated transition is, for example, fading, by which the color becomes gradually lighter. It should be noted that the transition effect may be ignored or replaced with another effect unless the reproduction apparatus has a capability of performing the designated effect.

[0301] When the still picture displayed is erased, the start section transition mode of the DLIST of the next still picture is acquired. When the transition mode is "no transition", the next still picture is immediately displayed. When the transition mode is not "no transition", i.e., when the transition effect is designated, the next still picture is displayed with an effect. Thus, the still pictures are switched. At this point, the highlight information and the sub-picture information already read in the buffer are decoded as well as the video information included in the P\_VOB.

[0302] The processing in response to the key operations by the user is performed as shown in Figure 64. When the key operation accompanies a change of the audio program, i.e., when the key operation is for NextProgram (reproduction of the next audio program), PrevProgram (reproduction of the previous audio program), reproduction of the designated audio program, reproduction of the audio program by a command after the menu is retrieved, or a change of the audio cell, the audio cell of the audio program to be reproduced is changed and processing for reproducing the audio cell is performed (Figure 65).

[0303] When the key operation by the user is for a change of only the still picture, i.e., the key operation is for NextDLIST (display of the next DLIST), PrevDLIST (display of the previous still picture), or display of the designated DLIST, the designated still picture is selected and processing for reproducing the still picture is performed only when the audio still video display mode of the designated still picture is Browsable (Figure 66).

[0304] In response to other key operations, the designated operation is performed without changing the audio output or still picture output. Such operations include display of the reproduction state and switching of the time display mode. In order to reproduce another stream (VOB) such as retrieval of the menu, the audio output and still picture display are terminated and the apparatus is switched to decode the VOB.

[0305] Thus, all the titles are reproduced and the operation is stopped. In accordance with specific setting of the DVD player or the DVD, only one title can be reproduced before the operation is stopped, or a menu can be displayed after reproduction of one or more titles is completed.

[0306] Hereinafter, the control of the video decoder and video buffer performed by the synchronization adjusting section 102 will be additionally described.

[0307] Since data of a still picture is already stored in the buffer memory, the display of the still picture is managed based on the position in the buffer memory at which the still picture of the designated cell of the designated program is recorded or based on the ordinal number (i.e., first, second, etc.) of the still picture with respect to the start. When the management is performed based on the position in the buffer memory, the data is sent to the video decoder 87 from the designated address in the video buffer 96 and displayed by an instruction of the synchronization adjusting section 102. When the management is performed based on the ordinal number of the still picture, the data stored in the video buffer 96 from the leading end thereof is sent to the video decoder 87 and the display is switched when the designated ordinal number is reached. When the still picture is switched, display effects can be added by designating the transition mode. The time to switch the still picture can be designated on a program-by-program basis before and after the display of the still picture. However, in the case where the reproduction apparatus does not have a special effect display function, the still picture can simply be switched with the display effects being ignored.

[0308] In a synchronous mode (SlideShow), the audio data is decoded by the audio decoder 100, and the still picture, highlight and sub-picture are reproduced in accordance with the "display timing". The synchronization adjusting section 102 compares the reference time of the system and the "display timing" from the system control section 93 and control the synchronization.

[0309] In this case, switching of only the display by the user is prohibited. SlideShow is effectively used, for example, for displaying lyrics along with the music and displaying a still picture in a moving picture. In the asynchronous mode (Browsable), audio data is not synchronized with and reproduced separately from highlight data, sub-picture data and still picture data. The highlight data, sub-picture data and still picture data are synchronized to one another, and the audio data is continuously reproduced in realtime based on the time

information of the system. The still picture is switched in the asynchronous mode by the user operation and the command. The user operation basically are, for example, an operation of continuously reproducing audio programs while feeding display list (DLIST) forward, backward or to the leading end; and an operation of feeding both audio programs and display list (DLIST) simultaneously forward, backward or to the leading end. The command has similar functions. In this case, the "display timing" is considered as the display continuation time period of the still picture. When the interaction from the user is not generated during the time period of the "display timing", a still picture is displayed based on the next DLIST.

[0310] Browsable is effectively used, for example, for displaying photos in a switching manner while music is reproduced and displaying various types of information including an explanation about the music and information on the people involved in a switching manner.

[0311] The synchronous mode and the asynchronous mode are switched over in accordance with the picture program reproduction control. The audio still video display mode of the audio program information can be designated so that some of the audio programs included in the audio title are randomly selected and repeated a designated number of times or such audio programs are repeated a designated number of times prohibiting repetition of the same program (shuffle mode).

[0312] The AV decoder section 85c can have other structures.

[0313] As shown in Figure 67, the system decoders for AOB, P\_VOB and VOB can be replaced with a single system decoder 109 having the functions of these decoders. Since the AOB is input at different timing from the P\_VOB and VOB, a system decoder which is substantially the same as that specified by DVD-Video is usable except that the buffer memory capacities of the highlight buffer 94, the video buffer 96 and the sub-picture buffer 105 are increased and that a management mechanism for a still picture is added to control of the video buffer 96. An AV decoder section 85d shown in Figure 67 operates in substantially the same manner as the AV decoder section 85c shown in Figure 61.

[0314] As shown in Figure 68, the P\_VOB buffer 106 for P\_VOB can be provided immediately before the AV decoder section 85d. The same type of AV decoder section as used by DVD-Video is usable. All the P\_VOB data to be read before the reproduction of the audio data is stored in the P\_VOB buffer 106. The P\_VOB buffer 106 dynamically multiplexes the P\_VOBS corresponding to the reproduction order with the audio stream and sends the resultant data to the AV decoder section 85d. Accordingly, the system decoder 109 for AOB and P\_VOB in the AV decoder section 85d is required to have a processing speed which is slightly higher than the speed specified by the DVD-Video standards. Streams need to be supplied to the AV decoder section 85d so that the audio buffer 99 does

not underflow.

[0315] In the third example, as described above, program reproduction information including the start time and reproduction time period of each piece of audio data based on the reproduction start time of the leading audio data in the MPEG2 stream is recorded in the management region as a part of the reproduction control information. Accordingly, an optical disk for realizing reproduction of high quality digital audio data along with the video data in a restricted range of bit rates is provided. Moreover, a certain interval between audio reproductions can be maintained even in an inexpensive reproduction apparatus including no video data reproduction function. This allows title creators to create data easily.

[0316] Since a plurality of still pictures, sub-picture and menu can be displayed synchronously with or asynchronously from high quality audio data, a wider variety of displays become available.

[0317] According to the present invention, reproduction order information defining the order of the video streams to be reproduced synchronously with an audio sequence is recorded on a recording medium. By changing the contents of the reproduction order information, the contents of the video streams reproduced synchronously with the audio sequence can easily be changed. This provides the title creators with the freedom of creating a variety of video streams for one audio sequence, and provides the user with the freedom of selecting a desired video stream among a plurality of video streams offered for one audio sequence.

[0318] According to the present invention, video reproduction mode information is recorded on the recording medium. Whether it is possible or not to change the order of the video stream to be reproduced in synchronization with the audio sequence based on interaction from a user is adjusted by the video reproduction mode information. The video reproduction mode information enables the switching of the reproduction timing/reproduction time period of the video stream to be reproduced synchronously with the audio sequence. Thus, the two different types of video reproduction modes, i.e., "SlideShow" and "Browsable" can be offered to the user.

[0319] According to the present invention, prior to the reproduction of the audio sequence, a video stream to be reproduced synchronously with the audio sequence is buffered in the buffer provided in the reproduction apparatus. By guaranteeing the range of the recording medium to read to the buffer, reproduction by any reproduction apparatus is guaranteed. As a result, title creators can easily assume the situation in which titles are reproduced, which facilitates the production of the titles. Consequently, the high quality titles can be supplied at lower cost.

[0320] According to the present invention, a non-MPEG stream can be decoded by an MPEG2 decoder. Thus, the reproduction apparatus can be provided at



lower cost.

[0321] Various other modifications will be apparent to and can be readily made by those skilled in the art without departing from the scope and spirit of this invention. Accordingly, it is not intended that the scope of the claims appended hereto be limited to the description as set forth herein, but rather that the claims be broadly construed.

## Claims

### 1. A data storage medium having stored thereon:

an audio sequence including at least one audio stream;  
at least one video stream; and  
reproduction control information for controlling reproduction of the at least one audio stream and the at least one video stream,  
wherein the reproduction control information includes reproduction order information defining the order of at least one video stream, among the at least one video stream stored on the data storage medium, which is to be reproduced in synchronization with the audio sequence.

2. A data storage medium according to claim 1, wherein the reproduction control information further includes video reproduction mode information indicating whether it is possible or not to change the order of the at least one video stream to be reproduced in synchronisation with the audio sequence based on interaction from a user.

3. A data storage medium according to claim 1, wherein the reproduction control information further includes video reproduction mode information indicating whether reproduction timing of the at least one video stream to be reproduced in synchronization with the audio sequence is defined or a reproduction time period thereof is defined.

4. A data storage medium according to claim 1, wherein the reproduction control information further includes reproduction order mode information defining whether the at least one video stream, the order of which is defined by the reproduction order information, is reproduced randomly or sequentially.

5. A data storage medium according to claim 4, wherein the reproduction order mode information indicates whether the at least one video stream is reproduced randomly while permitting overlap or randomly while prohibiting overlap.

6. A data storage medium according to claim 1,

wherein the audio sequence corresponds to at least one program, and the at least one video stream stored on the data storage medium is grouped on a program-by-program basis.

7. An apparatus for reproducing information from a data storage medium having stored thereon an audio sequence including at least one audio stream; at least one video stream; and reproduction control information for controlling reproduction of the at least one audio stream and the at least one video stream, wherein the reproduction control information includes reproduction order information defining the order of at least one video stream, among the at least one video stream stored on the data storage medium, which is to be reproduced in synchronization with the audio sequence, the apparatus comprising:

a reading section for reading the audio sequence and the at least one video stream stored on the data storage medium; and  
a reproduction section for reproducing the at least one video stream in synchronization with the audio sequence in the order defined by reproduction order information.

8. An apparatus according to claim 7, wherein the reproduction control information further includes video reproduction mode information indicating whether it is possible or not to change the order of the at least one video stream to be reproduced in synchronisation with the audio sequence based on interaction from a user.

9. An apparatus according to claim 7, wherein the reproduction control information further includes video reproduction mode information indicating whether reproduction timing of the at least one video stream to be reproduced in synchronization with the audio sequence is defined or a reproduction time period thereof is defined.

10. An apparatus according to claim 7, wherein the reproduction control information further includes reproduction order mode information defining whether the at least one video stream, the order of which is defined by the reproduction order information, is reproduced randomly or sequentially.

11. An apparatus according to claim 10, wherein the reproduction order mode information indicates whether the at least one video stream is reproduced randomly while permitting overlap or randomly while prohibiting overlap.

12. An apparatus according to claim 7, wherein the at least one video stream to be reproduced in syn-

chronization with the audio sequence is buffered into a buffer located in the reproduction apparatus before reproduction of the audio sequence.

13. A method for reproducing information from a data storage medium having stored thereon an audio sequence including at least one audio stream; at least one video stream; and reproduction control information for controlling reproduction of the at least one audio stream and the at least one video stream, wherein the reproduction control information includes reproduction order information defining the order of at least one video stream, among the at least one video stream stored on the data storage medium, which is to be reproduced in synchronization with the audio sequence, the method comprising the steps of:
  - reading the audio sequence and the at least one video stream stored on the data storage medium; and
  - reproducing the at least one video stream in synchronization with the audio sequence in the order defined by reproduction order information.
14. A method according to claim 13, wherein the reproduction control information further includes video reproduction mode information indicating whether it is possible or not to change the order of the at least one video stream to be reproduced in synchronization with the audio sequence based on interaction from a user.
15. A method according to claim 13, wherein the reproduction control information further includes video reproduction mode information indicating whether reproduction timing of the at least one video stream to be reproduced in synchronization with the audio sequence is defined or a reproduction time period thereof is defined.
16. A method according to claim 13, wherein the reproduction control information further includes reproduction order mode information defining whether the at least one video stream, the order of which is defined by the reproduction order information, is reproduced randomly or sequentially.
17. A method according to claim 16, wherein the reproduction order mode information indicates whether the at least one video stream is reproduced randomly while permitting overlap or randomly while prohibiting overlap.
18. A method according to claim 13, wherein the at least one video stream to be reproduced in synchronization with the audio sequence is buffered

into a buffer located in the reproduction apparatus before reproduction of the audio sequence.

19. A data storage medium stored with a first system stream and a second system stream to be reproduced in synchronization with each other, wherein:

the first system stream includes reproduction control information indicating timing at which the first system stream is reproduced, and the second system stream is reproduced at timing determined by information other than information included in the second system stream.

20. An apparatus for reproducing a data storage medium stored with a first system stream and a second system stream to be reproduced in synchronization with each other, wherein the first system stream includes reproduction control information indicating timing at which the first system stream is reproduced, the apparatus comprising:


a reading section for reading the first system stream and the second system stream stored on the data storage medium; and a decoder section for decoding the first system stream in accordance with the reproduction control information, wherein the second system stream is decoded in accordance with a control signal supplied from outside of the decoder section.

21. A method for reproducing a data storage medium stored with a first system stream and a second system stream to be reproduced in synchronization with each other, wherein the first system stream includes reproduction control information indicating timing at which the first system stream is reproduced, the method comprising the steps of:


reading the first system stream and the second system stream stored on the data storage medium; and controlling the timing at which the first system stream is reproduced in accordance with the reproduction control information; controlling the timing at which the second system stream is reproduced in accordance with information other than information included in the second system stream.




**FIG. 1A**




**FIG. 1B**





**FIG. 1C**



**FIG. 1D**



**FIG. 2A****FIG. 2B**




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9






FIG. 10

	Physical allocation information	Time attribute information	Start cell number	Still picture flag	Reproduction start audio time	Program reproduction time period	Audio pause time period
Program #1	No-Continue	No-Continue	1	Exist	90,000	5,490,000	90,000
Program #2	Continue	Continue	4	Exist	5,580,000	10,890,000	90,000
Program #3	No-Continue	No-Continue	8	none	90,000	5,490,000	90,000
Program #4	Continue	Continue	10	none	5,580,000	5,490,000	90,000
Program #5	Continue	Continue	12	none	11,160,000	5,400,000	0

**FIG. 11**

	Cell index	Cell type	Start address	Termination address
Cell #1	0	Still	26,592	26,703
Cell #2	0	Silent	26,704	26,799
Cell #3	1	Audio	26,800	32,559
Cell #4	0	Still	32,560	32,671
Cell #5	0	Silent	32,672	32,767
Cell #6	1	Audio	32,768	38,527
Cell #7	2	Audio	38,528	44,287
Cell #8	0	Silent	0	95
Cell #9	1	Audio	96	14,975
Cell #10	0	Silent	14,976	15,071
Cell #11	1	Audio	15,072	20,831
Cell #12	2	Audio	20,832	26,591

**FIG. 12A****FIG. 12B**






**FIG. 13A****FIG. 13B****FIG. 14**

FIG. 15




FIG. 16




FIG. 17





FIG. 18









FIG. 20





*FIG. 21*

FIG. 22



54




FIG. 24




FIG. 25






FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32

	Physical allocation information	Time attribute information	Start cell number	Reproduction start audio time	Program reproduction time period	Audio pause time period
Program #1	No-Continue	No-Continue	1	90,000	5,490,000	90,000
Program #2	Continue	Continue	3	5,580,000	10,890,000	90,000
Program #3	No-Continue	No-Continue	6	90,000	5,490,000	90,000
Program #4	Continue	Continue	8	5,580,000	5,490,000	90,000
Program #5	Continue	Continue	10	11,160,000	5,400,000	0



FIG. 33

	Used SR number	Initial button number	Picture transition mode	Still picture identification code	Picture cell start PTS	Picture program reproduction time period	Start section transition time period	Termination section transition time period
Picture program #1	0	1	1	XXXXXXX	45,000	5,490,000	352	352
Picture program #2	0	2	1	XXXXXXX	45,000	10,890,000	352	352
Picture program #3	0	3	1	XXXXXXX	45,000	5,490,000	352	352
Picture program #4	0	4	2	XXXXXXX	45,000	5,490,000	352	352
Picture program #5	0	5	2	XXXXXXX	45,000	5,400,000	352	352

**FIG. 34**

	Cell index	Cell type	Start address	Termination address
Cell #1	0	Silent	0	95
Cell #2	1	Audio	96	14,975
Cell #3	0	Silent	14,976	15,071
Cell #4	1	Audio	15,072	20,831
Cell #5	2	Audio	20,832	26,591
Cell #6	0	Silent	26,592	26,687
Cell #7	1	Audio	26,688	41,567
Cell #8	0	Silent	41,568	41,663
Cell #9	1	Audio	41,664	56,539
Cell #10	2	Audio	56,540	51,419

**FIG. 35**

	Start address	Termination address
Picture cell #1	51,420	51,469
Picture cell #2	51,470	51,519
Picture cell #3	51,520	51,569
Picture cell #4	51,570	51,619
Picture cell #5	51,620	51,669



**FIG. 36A****FIG. 36B**

FIG. 37




FIG. 38





FIG. 39



*FIG. 40*





FIG. 41






*FIG. 42*

FIG. 4.3





FIG. 44







FIG. 46



**FIG. 47**




FIG. 48




FIG. 49







FIG.50



Display timing mode    00b: SlideShow  
                          01b: Browseable  
                          Others: reserved

Display order mode    00b: Sequential  
                          01b: Random  
                          11b: Shuffle  
                          Others: reserved

FIG. 51




FIG. 52




FIG. 53




FIG. 54

	Physical allocation information	Time attribute information	Start cell number	Reproduction start audio time	Program reproduction time period	Audio pause time period	ASVU number	Still video display mode	ATS_ASV_PBI start address	ATS_ASV_PBI termination address
Program #1	No-Continue	No-Continue	1	90,000	5,490,000	90,000	1	SlideShow	(Leading end of #1)	(Trailing end of #1)
Program #2	Continue	No-Continue	3	90,000	10,890,000	90,000	1	SlideShow	(Leading end of #1)	(Trailing end of #1)
Program #3	No-Continue	No-Continue	6	90,000	5,490,000	90,000	2	Browsable	(Leading end of #2)	(Trailing end of #2)
Program #4	Continue	Continue	8	5,490,000	5,400,000	0	2	Browsable	(Leading end of #2)	(Trailing end of #2)

**FIG.55**

Example of still video reproduction information #1

	ASV number	Initial button number	Audio program number	Display timing	Start section display effect	Start section transition time period	Termination section display effect	Termination section transition time period
Display list #1	1	1	1	90,000	1	352	1	352
Display list #2	2	2	2	90,000	1	352	1	352
Display list #3	3	3	2	5,580,000	1	352	2	352

Example of still video reproduction information #2

	ASV number	Initial button number	Audio program number	Display timing	Start section display effect	Start section transition time period	Termination section display effect	Termination section transition time period
Display list #1	4	4	3	5,490,000	2	352	2	352
Display list #2	5	5	4	5,400,000	2	352	2	352

*FIG. 56*

	Cell index	Cell type	Start address	Termination address
Cell #1	0	Silent	0	95
Cell #2	1	Audio	96	14,975
Cell #3	0	Silent	14,976	15,071
Cell #4	1	Audio	15,072	20,831
Cell #5	2	Audio	20,832	26,591
Cell #6	0	Silent	26,592	26,687
Cell #7	1	Audio	26,688	41,567
Cell #8	2	Audio	41,568	56,443

**FIG. 57**

	ASV start address
ASV search pointer #1	0
ASV search pointer #2	50
ASV search pointer #3	100
ASV search pointer #4	150
ASV search pointer #5	200


**FIG. 58**

	Number of P_VOBS	Start P_VOB number
ASVU general information #1	3	1
ASVU general information #2	2	4




**FIG. 59A**

SlideShow

**FIG. 59B**

Browsable




**FIG. 60**

FIG. 61





FIG. 62




**FIG. 63**

FIG. 64




FIG. 65




FIG. 66






FIG. 67




FIG. 68





FIG. 69





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 99 10 4877

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP 0 798 722 A (PIONEER ELECTRONIC CORPORATION) 1 October 1997 (1997-10-01) * page 4, line 56 - page 5, line 53 * * page 6, line 36 - page 7, line 23 * * page 12, line 12 - line 26; figures 1,3,4,8A,8B *	1,7,13,19-21	H04N9/806
P,A	EP 0 847 198 A (MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD) 10 June 1998 (1998-06-10) * page 13, line 51 - page 18, line 12; figures 1,16-22 * & WO 97 13365 A	1,7,13,19-21	
A			
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04N
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 21 July 1999	Examiner Verleye, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document	

EPO FORM 1503 03.92 (P4C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 10 4877

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-07-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 798722 A	01-10-1997	JP 9259573 A	03-10-1997
		CN 1173698 A	18-02-1998
EP 847198 A	10-06-1998	DE 69602273 D	02-06-1999
		CN 1197572 A	28-10-1998
		EP 0918438 A	26-05-1999
		WO 9713365 A	10-04-1997
		US 5784528 A	21-07-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82